

ANSI X3H2-95-486
ISO/IEC JTC1/SC21/WG3 DBL LHR-?

I S O
INTERNATIONAL ORGANIZATION FOR STANDARDIZATION
ORGANISATION INTERNATIONALE DE NORMALISATION

December 6, 1995

Subject: SQL3 Part 7: Temporal
Status: Change Proposal
Title: Response to LHR-042, "Possible problems in SQL/T"
Version: 1
Source: ANSI Expert's Contribution
Author: Richard T. Snodgrass
Abstract: This change proposal addresses the concerns listed in LHR-042. It also addresses the possible problems with SQL/Temporal listed in LHR-009, numbered **TMPRL-001** through **TMPRL-012**.

References:

- | | | |
|----|--|------------------|
| 1 | Valid-Time Support in SQL3 | |
| 2 | Comments on SQL/Temporal | YOW-155 |
| 3 | Proposal for a New SQL Part — Temporal | RIO-075 |
| 4 | SQL/Bindings | LHR-007 |
| 5 | SQL/Temporal | LHR-009 |
| 6 | Possible Problems in SQL/T | LHR-042 |
| 7 | Fixing some possible problems in SQL/T | LHR-043 |
| 8 | Clarify assignment rules for datetimes | LHR-046 |
| 9 | Response to LHR-043 | ANSI X3H2-95-487 |
| 10 | The TSQL2 Temporal Query Language | Kluwer |

LHR-042 is a recasting of the comments that originally appeared in YOW-155. In LHR-042, the problems are grouped into sixteen categories.

In this document, we address these problems, following the same numbered categories. In many cases, the problems are eliminated with changes to the base document, indicated with

In Section ..., replace “...” with “...”.

Some of these changes were suggested by LHR-043, in a different form.

This document should be read with LHR-042 in hand, as we do not repeat many of the statements made in that document.

We then address the possible problems with SQL/Temporal listed in LHR-009, numbered **TMPRL-001** through **TMPRL-012**.

We thank the author of LHR-042, J.M. Sykes, for his careful reading of the SQL/Temporal base document.

1 Definitions

- *“P is not specified”* In Section 3.1, replace “**period**: a set of contiguous granules of a specified precision.” with “**period**: a set of contiguous granules of a specified precision *P*.”
- *“it is not made clear whether it is a quantum period, or an instant.”* This question has far-ranging philosophical implications. Philosophers have argued for ages whether time is discrete (in which time is viewed as being isomorphic to the integers, which each integer corresponding to a “point” in time), dense (in which time is viewed as being isomorphic to the rationals), or continuous (in which time is viewed as being isomorphic to the real numbers). Science and metaphysics have yet to determine which model best fits reality; good arguments can be made for each of the three models. In terms of the TSQL2 language, we view this choice as largely unimportant; time can be either continuous, dense, or discrete. However, since we are modeling time on a discrete computing device, our “view” of time and the uses to which we put that view must necessarily be discrete. Hence, we speak in terms of “granules” instead of instants. This topic is discussed in detail in [1,10].

2 Extensibility

- *“The syntax of <data type>, when used to specify a period ... seems unnecessarily restrictive that there is no provision for periods corresponding to the other SQL datetime data types, DATE and TIME.”* TSQL2 contains provision to specify the range and precision of a period, and encompasses DATES, i.e., periods with a precision of DAY, and TIME, i.e., periods with a range of 24 HOURS and a precision of SECOND. [1,10] give the details. The extended PERIOD declaration syntax will be included in a separate change proposal, where it will be integrated in a consistent fashion with calendars other than the default Gregorian calendar.

The use of a data type generator is limited to defining period analogues of **TIMESTAMP**, **TIME**, and **DATE**. It does not allow one to specify other ranges, such as a century (instead of the 99 centuries in **DATE** and **TIMESTAMP**) nor other ranges, such as **MONTH**.

3 Assignability and comparability

- *“This interpretation, if correct, it is inconsistent with the approach usually followed in SQL.”* As noted in LHR-046 [8], the same statement can be made concerning SQL’s datetime types. The intent was that the period type would behave identically to the datetime types in this aspect. When the semantics of datetime types has been resolved, the same changes should be applied to the period type. In the meantime, the SQL/Temporal base document is consistent with the SQL/Foundation base document.

4 Ordering of periods

- “*There is no specification of a less-than operation for values of data type period.*” Section 7.4 “<precedes predicate>” of the SQL/Temporal base document provides such an operation. However, the ORDER BY operation discussed Section 13.1 “<declare cursor>” of the SQL3/Foundation base document uses the <comparison> predicate of Section 8.2 “<comparison predicate>” to define the semantics of ordering. The following general rule should be added to Section 7.2 “<comparison predicate>” of the base document of SQL/Temporal.

“2) The comparison of two periods is determined using PRECEDES. Let X and Y be the two values to be compared and let H be the finest precision of X and Y . The result of $X < Y$ is defined as X PRECEDES Y and the result of $X > Y$ is defined as Y PRECEDES X .”

5 5.2 literal

- “*GR1, last few words are “...as the period”; what period?*” The delimiting timestamps must have the same precision, as specified by SR3 of that section. In Section 5.2, replace GR1 “The beginning and ending delimiting timestamps of a period shall have the same precision as the period.” with “The period literal shall have a precision equal to that of the beginning delimiting timestamp.”.
- “*GR4...should be moved to 6.1 <data type>...It should also be amended to prohibit null delimiting timestamps.*” We agree. GR4 of Section 5.2 “<literal>” should be moved to Section 6.1 “<data type>”, and the following sentence added to that general rule: “If the beginning delimiting timestamp or the ending delimiting timestamp is null, then an exception condition is raised: *data exception — invalid period format.*”

6 6.2 <set function specification>

- “*Period is the only data type for which MIN or MAX may return a value that is not in the grouped table. Specification of ordering would remove this anomaly.*” Ordering is specified in GR2 using precedes. In Section 6.2, remove SR2 and GR1–3.

7 6.4 <period value function>

- “*GR2f is redundant.*” We agree. GR2f should be discarded.

8 6.5 <cast specification>

- “*The ability to cast from period to DATE or TIMESTAMP seems of small utility, especially in comparison with some of the features left out. Moreover, it does not conform to the generally accepted meaning of ‘cast’, as ‘convert to the equivalent value of some other data type’.*” While it may be of small utility, it was included for completeness. The definition seems to be a natural one, and attempts to capture what the “equivalent” DATE or TIMESTAMP is for a given period.

9 6.5 <cast specification>

- “*[the term ‘duration’] is not defined*” Each period contains at least one granule, so the duration of the smallest period literal is one granule in the precision of that literal. However, we agree that the use of the term ‘duration’ is confusing.

In Section 6.5 “<cast specification>”, replace GR1b) and GR1c) with the single GR1b): “If SD is the datetime date type DATE or TIMESTAMP, then the conversion results in the value PERIOD(SV , SV).”

10 Duration of a period (<interval value expression>?)

- “There is no explicit way to obtain the value of the interval that represents the duration of a period.” This was an omission; that capability was present in RIO-75. To the table in SR3 of Section 6.5 “<cast specification>”, add entries M to cells (P,YM) and (P,DT). Add the following as subitems under GR3 to this section:

“c) If TD is the data type year-month INTERVAL, then let Q be the least significant <datetime field> of TD . The result of the conversion is the result of:

$CAST((END(SV) - BEGIN(SV)) MONTH AS INTERVAL Q) + INTERVAL '1' Q$ ”

“d) If TD is the data type day-time INTERVAL, then let Q be the least significant <datetime field> of TD . The result of the conversion is the result of:

$((END(SV) - BEGIN(SV)) Q) + INTERVAL '1' Q$ ”

11 7.2 <comparison predicate>

- “In General Rule 1a iv, ‘ $X - Y$ ’ should presumably read ‘ $X = Y$ ’.” We agree. The October, 1995 version (LHR-009) [5] has already incorporated that correction.

12 7.3 <overlaps predicate>: incompatibility

- “See the Editor’s note.” This is indeed incompatible. The intent was to extend the allowable arguments to OVERLAPS to include as an argument a period, a single datetime, a periods denoted with a pair of datetimes or period denoted with a datetime-interval pair, with the one exception of both arguments being single datetimes not allowed.

See the Appendix for a replacement of the entire Section 7.3 “<overlaps predicate>”.

13 7.3 <overlaps predicate>: data type of <row value expression>

See the Appendix for a replacement of subclauses 7.3, 7.4, 7.5 and 7.6.

14 7.3 <overlaps predicate>: result

- “We would expect the result to be true also in the case that $B1 \geq E2$ AND $B2 \geq E2$.” If $B1-E2$, the result is true according to the original prose. If $B1 > E2$, then the first period is strictly after the second period, and thus the two periods do not overlap.

15 7.6 <meets predicate>

We agree. See the appendix.

16 Other Parts of the SQL Standard

- “There are no provisions for dealing with items of data type period in SQL/Bindings.” This requires several additions to SQL/Bindings [4].
 - Add entry PERIOD, with Code 11, to Table 2 “Codes used for SQL data types in Dynamic SQL”.
 - Rename Table 3 to “Codes associated with datetime and period data types in Dynamic SQL”. Add entries PERIOD, with Code 6, and PERIOD WITH TIME ZONE, with Code 7.

- In Section 12.1 “Description of SQL item descriptor areas”, add to SR3: “n) TYPE indicates a <period type>, DATETIME_INTERVAL_CODE is a code specified in Table 3, “Codes associated with datetime and period data types in Dynamic SQL”, and PRECISION is a valid value for the <period precision> of the indicated period datatype.
- In Section 12.5 “<set descriptor statement>”, add to GR5: “n) If V indicates PERIOD, or PERIOD WITH TIME ZONE, then PRECISION is set to 6 and all other item descriptor area fields are set to implementation-dependent values.”
- In Section 12.9 “<using clause>”, add to GR3.f.v, GR4.f.v and GR5.f.v: “12) If TYPE indicates a <period type>, then LENGTH is set to the length in positions of the period type, DATETIME_INTERVAL_CODE is set to a code as specified in Table 3, “Codes associated with datetime and period data types in Dynamic SQL”, to indicate the specific datetime data type, and PRECISION is set to the <period precision>, if applicable.” Add to GR6.f.v: “9) If TYPE indicates a <period type>, then LENGTH is set to the length in positions of the datetime type, DATETIME_INTERVAL_CODE is set to a code as specified in Table 3, “Codes associated with datetime and period data types in Dynamic SQL”, to indicate the specific datetime data type, and PRECISION is set to the <period precision>, if applicable.”

17 Problems Listed in LHR-009

This section considered the possible problems listed in the SQL/Temporal base document, and numbered **TMPRL-001** through **TMPRL-012**. As these problems were primarily drawn from YOW-155, there is substantial duplication with the problems discussed above. Nevertheless, we include all of them here for completeness.

17.1 TMPRL-001

See Section 16 of this document.

17.2 TMPRL-002

See Section 3 of this document.

17.3 TMPRL-003

See Section 4 of this document.

17.4 TMPRL-004

See Section 5 of this document.

17.5 TMPRL-005

While the recommended change is not consistent with the syntax rules for other data types, we agree with the desire for generality. Replace SR3 of Section 6.1 “<data type>” with “3) The length of a period is the number of characters sufficient to hold the longest result of CAST(whatever TO CHARACTER) for a value of the data type.”

17.6 TMPRL-006

See Section 6 of this document.

17.7 TMPRL-007

See Section 7 of this document.

17.8 TMPRL-008

See Section 8 of this document.

17.9 TMPRL-009

See Sections 9 and 10 of this document.

17.10 TMPRL-0010

See Section 11 of this document.

17.11 TMPRL-0011

See Sections 12 and 13 of this document.

17.12 TMPRL-00124

See Section 15 of this document.

18 Summary

This change proposal has made some specific change recommendations, thereby addressing all known concerns related to LHR-009.

A Replaced Sections

The following sections should replace Sections 7.3, 7.4, 7.5 and 7.6, respectively. They generalize these operators to apply to all reasonable combinations of period, datetime, and row value expressions.

A.1 <overlaps predicate>

Function

Specify a test for an overlap between two periods, or between a period and a datetime.

Format

<overlaps predicate> ::=
 <period or datetime value expression 1> **OVERLAPS** <period or datetime value expression 2>

<period or datetime value expression 1> ::= <period or datetime value expression>

<period or datetime value expression 2> ::= <period or datetime value expression>

<period or datetime value expression> ::= <row value expression>
 | <period value expression>
 | <datetime value expression>

Syntax Rules

1. Let <period or datetime value expression 1> be PD_1 and let <period or datetime value expression 2> be PD_2 .
2. If PD_1 is <row value expression>, then:
 - a) Let R_1 be the <row value expression> in PD_1 .
 - b) The degree of R_1 shall be 2.
 - c) Let T_1 be the type of the first column of R_1 , and T_2 be the type of the second column of R_1 . T_1 shall be a datetime data type.
 - d) If T_2 is a datetime data type, then it shall be comparable with T_1 .
 - e) If T_2 is INTERVAL, then the precision of T_2 shall be such that the interval can be added to T_1 .
 - f) The precision of PD_1 is the precision of T_1 .
3. If PD_1 is <period value expression> or <datetime value expression>, then the precision of PD_1 is that of the <period value expression> or the <datetime value expression>.
4. If PD_2 is <row value expression>, then:
 - a) Let R_2 be the <row value expression> in PD_2 .
 - b) The degree of R_2 shall be 2.
 - c) Let T_3 be the type of the first column of R_2 , and T_4 be the type of the second column of R_2 . T_3 shall be a datetime data type.
 - d) If T_4 is a datetime data type, then it shall be comparable with T_3 .
 - e) If T_4 is INTERVAL, then the precision of T_4 shall be such that the interval can be added to T_3 .
 - f) The precision of PD_2 is the precision of T_3 .
5. If PD_2 is <period value expression> or <datetime value expression>, then the precision of PD_2 is that of the <period value expression> or the <datetime value expression>.
6. The precision of PD_1 and PD_2 shall be identical.

7. PD_1 and PD_2 shall not both be datetime data types.

Access Rules

No additional Access Rules.

General Rules

1. Case:

- (a) If the data type of PD_1 is DATE, TIME, or TIMESTAMP, then let B_1 and E_1 both be the value of PD_1 .
- (b) If the data type of PD_1 is PERIOD, then let B_1 be the value of $BEGIN(PD_1)$ and E_1 be the value of $END(PD_1)$.
- (c) Otherwise, let R_1 be the value of <row value expression 1> and let B_1 be the value of the first column of R_1 .

Case:

- i) If the data type of the second column of R_1 is a datetime data type, then let E_1 be the value of the second column of R_1 .
 - ii) If the data type of the second column of R_1 is INTERVAL, then let I_1 be the value of the second column of R_1 . Let $E_1 = B_1 + I_1$.
2. If B_1 is the null value or if $E_1 < B_1$, then let $S_1 = E_1$ and let $T_1 = B_1$. Otherwise, let $S_1 = B_1$ and let $T_1 = E_1$.

3. Case:

- (a) If the data type of PD_2 is DATE, TIME, or TIMESTAMP, then let B_2 and E_2 both be the value of PD_2 .
- (b) If the data type of PD_2 is PERIOD, then let B_2 be the value of $BEGIN(PD_2)$ and E_2 be the value of $END(PD_2)$.
- (c) Otherwise, let R_2 be the value of <row value expression 2> and let B_2 be the value of the first column of R_2 .

Case:

- i) If the data type of the second column of R_2 is a datetime data type, then let E_2 be the value of the second column of R_2 .
 - ii) If the data type of the second column of R_2 is INTERVAL, then let I_2 be the value of the second column of R_2 . Let $E_2 = B_2 + I_2$.
4. If B_2 is the null value or if $E_2 < B_2$, then let $S_2 = E_2$ and let $T_2 = B_2$. Otherwise, let $S_2 = B_2$ and let $T_2 = E_2$.

5. The value of the <overlaps predicate> is the result of the following expression:

($S_1 > S_2$ AND NOT ($S_1 \geq T_2$ AND $T_1 \geq T_2$))
 OR
 ($S_2 > S_1$ AND NOT ($S_2 \geq T_1$ AND $T_2 \geq T_1$))
 OR
 ($S_1 = S_2$)

A.2 <precedes predicate>

Function

Specify a test for one period or datetime preceding a second period or datetime.

Format

<precedes predicate> ::=
 <period or datetime value expression 1> **PRECEDES** <period or datetime value expression 2>

Syntax Rules

1. Let <period or datetime value expression 1> be PD_1 and let <period or datetime value expression 2> be PD_2 .
2. If PD_1 is <row value expression>, then:
 - a) Let R_1 be the <row value expression> in PD_1 .
 - b) The degree of R_1 shall be 2.
 - c) Let T_1 be the type of the first column of R_1 , and T_2 be the type of the second column of R_1 . T_1 shall be a datetime data type.
 - d) If T_2 is a datetime data type, then it shall be comparable with T_1 .
 - e) If T_2 is INTERVAL, then the precision of T_2 shall be such that the interval can be added to T_1 .
 - f) The precision of PD_1 is the precision of T_1 .
3. If PD_1 is <period value expression> or <datetime value expression>, then the precision of PD_1 is that of the <period value expression> or the <datetime value expression>.
4. If PD_2 is <row value expression>, then:
 - a) Let R_2 be the <row value expression> in PD_2 .
 - b) The degree of R_2 shall be 2.
 - c) Let T_3 be the type of the first column of R_2 , and T_4 be the type of the second column of R_2 . T_3 shall be a datetime data type.
 - d) If T_4 is a datetime data type, then it shall be comparable with T_3 .
 - e) If T_4 is INTERVAL, then the precision of T_4 shall be such that the interval can be added to T_3 .
 - f) The precision of PD_2 is the precision of T_3 .
5. If PD_2 is <period value expression> or <datetime value expression>, then the precision of PD_2 is that of the <period value expression> or the <datetime value expression>.
6. The precision of PD_1 and PD_2 shall be identical.

Access Rules

No additional Access Rules.

General Rules

1. Case:
 - (a) If the data type of PD_1 is DATE, TIME, or TIMESTAMP, then let B_1 and E_1 both be the value of PD_1 .
 - (b) If the data type of PD_1 is PERIOD, then let B_1 be the value of $BEGIN(PD_1)$ and E_1 be the value of $END(PD_1)$.

- (c) Otherwise, let R_1 be the value of <row value expression 1> and let B_1 be the value of the first column of R_1 .

Case:

- i) If the data type of the second column of R_1 is a datetime data type, then let E_1 be the value of the second column of R_1 .
- ii) If the data type of the second column of R_1 is INTERVAL, then let I_1 be the value of the second column of R_1 . Let $E_1 = B_1 + I_1$.

2. If E_1 is the null value or if $E_1 < B_1$, then let $T_1 = B_1$. Otherwise, let $T_1 = E_1$.

3. Case:

- (a) If the data type of PD_2 is DATE, TIME, or TIMESTAMP, then let B_2 and E_2 both be the value of PD_2 .
- (b) If the data type of PD_2 is PERIOD, then let B_2 be the value of $BEGIN(PD_2)$ and E_2 be the value of $END(PD_2)$.
- (c) Otherwise, let R_2 be the value of <row value expression 2> and let B_2 be the value of the first column of R_2 .

Case:

- i) If the data type of the second column of R_2 is a datetime data type, then let E_2 be the value of the second column of R_2 .
- ii) If the data type of the second column of R_2 is INTERVAL, then let I_2 be the value of the second column of R_2 . Let $E_2 = B_2 + I_2$.

4. If B_2 is the null value or if $E_2 < B_2$, then let $S_2 = E_2$. Otherwise, let $S_2 = B_2$.

5. The value of the <precedes predicate> is the value of $T_1 < S_2$.

A.3 <contains predicate>

Function

Specify a test for a period containing another period or a datetime.

Format

<contains predicate> ::=
 <period or datetime value expression 1> **CONTAINS** <period or datetime value expression 2>

Syntax Rules

1. Let <period or datetime value expression 1> be PD_1 and let <period or datetime value expression 2> be PD_2 .
2. If PD_1 is <row value expression>, then:
 - a) Let R_1 be the <row value expression> in PD_1 .
 - b) The degree of R_1 shall be 2.
 - c) Let T_1 be the type of the first column of R_1 , and T_2 be the type of the second column of R_1 . T_1 shall be a datetime data type.
 - d) If T_2 is a datetime data type, then it shall be comparable with T_1 .
 - e) If T_2 is INTERVAL, then the precision of T_2 shall be such that the interval can be added to T_1 .
 - f) The precision of PD_1 is the precision of T_1 .
3. If PD_1 is <period value expression>, then the precision of PD_1 is that of the <period value expression>.
4. PD_1 shall not be a <datetime value expression>.
5. If PD_2 is <row value expression>, then:
 - a) Let R_2 be the <row value expression> in PD_2 .
 - b) The degree of R_2 shall be 2.
 - c) Let T_3 be the type of the first column of R_2 , and T_4 be the type of the second column of R_2 . T_3 shall be a datetime data type.
 - d) If T_4 is a datetime data type, then it shall be comparable with T_3 .
 - e) If T_4 is INTERVAL, then the precision of T_4 shall be such that the interval can be added to T_3 .
 - f) The precision of PD_2 is the precision of T_3 .
6. If PD_2 is <period value expression> or <datetime value expression>, then the precision of PD_2 is that of the <period value expression> or the <datetime value expression>.
7. The precision of PD_1 and PD_2 shall be identical.

Access Rules

No additional Access Rules.

General Rules

1. Case:
 - (a) If the data type of PD_1 is PERIOD, then let B_1 be the value of $BEGIN(PD_1)$ and E_1 be the value of $END(PD_1)$.
 - (b) Otherwise, let R_1 be the value of <row value expression 1> and let B_1 be the value of the first column of R_1 .
 Case:

- i) If the data type of the second column of R_1 is a datetime data type, then let E_1 be the value of the second column of R_1 .
 - ii) If the data type of the second column of R_1 is INTERVAL, then let I_1 be the value of the second column of R_1 . Let $E_1 = B_1 + I_1$.
- 2. If B_1 is the null value or if $E_1 < B_1$, then let $S_1 = E_1$ and let $T_1 = B_1$. Otherwise, let $S_1 = B_1$ and let $T_1 = E_1$.
- 3. Case:
 - (a) If the data type of PD_2 is DATE, TIME, or TIMESTAMP, then let B_2 and E_2 both be the value of PD_2 .
 - (b) If the data type of PD_2 is PERIOD, then let B_2 be the value of $BEGIN(PD_2)$ and E_2 be the value of $END(PD_2)$.
 - (c) Otherwise, let R_2 be the value of <row value expression 2> and let B_2 be the value of the first column of R_2 .
 Case:
 - i) If the data type of the second column of R_2 is a datetime data type, then let E_2 be the value of the second column of R_2 .
 - ii) If the data type of the second column of R_2 is INTERVAL, then let I_2 be the value of the second column of R_2 . Let $E_2 = B_2 + I_2$.
- 4. If B_2 is the null value or if $E_2 < B_2$, then let $S_2 = E_2$ and let $T_2 = B_2$. Otherwise, let $S_2 = B_2$ and let $T_2 = E_2$.
- 5. The value of the <contains predicate> is the result of the following expression:
 $S_1 \leq S_2$ AND $T_2 \leq T_1$

A.4 <meets predicate>

Function

Specify a test for one period or datetime adjoining another period or datetime.

Format

<meets predicate> ::=
 <period or datetime value expression 1> **MEETS** <period or datetime value expression 2>

Syntax Rules

1. Let <period or datetime value expression 1> be PD_1 and let <period or datetime value expression 2> be PD_2 .
2. If PD_1 is <row value expression>, then:
 - a) Let R_1 be the <row value expression> in PD_1 .
 - b) The degree of R_1 shall be 2.
 - c) Let T_1 be the type of the first column of R_1 , and T_2 be the type of the second column of R_1 . T_1 shall be a datetime data type.
 - d) If T_2 is a datetime data type, then it shall be comparable with T_1 .
 - e) If T_2 is INTERVAL, then the precision of T_2 shall be such that the interval can be added to T_1 .
 - f) The precision of PD_1 is the precision of T_1 .
3. If PD_1 is <period value expression> or <datetime value expression>, then the precision of PD_1 is that of the <period value expression> or the <datetime value expression>.
4. If PD_2 is <row value expression>, then:
 - a) Let R_2 be the <row value expression> in PD_2 .
 - b) The degree of R_2 shall be 2.
 - c) Let T_3 be the type of the first column of R_2 , and T_4 be the type of the second column of R_2 . T_3 shall be a datetime data type.
 - d) If T_4 is a datetime data type, then it shall be comparable with T_3 .
 - e) If T_4 is INTERVAL, then the precision of T_4 shall be such that the interval can be added to T_3 .
 - f) The precision of PD_2 is the precision of T_3 .
5. If PD_2 is <period value expression> or <datetime value expression>, then the precision of PD_2 is that of the <period value expression> or the <datetime value expression>.
6. The precision of PD_1 and PD_2 shall be identical.

Access Rules

No additional Access Rules.

General Rules

1. Case:
 - (a) If the data type of PD_1 is DATE, TIME, or TIMESTAMP, then let B_1 and E_1 both be the value of PD_1 .
 - (b) If the data type of PD_1 is PERIOD, then let B_1 be the value of $BEGIN(PD_1)$ and E_1 be the value of $END(PD_1)$.

- (c) Otherwise, let R_1 be the value of <row value expression 1> and let B_1 be the value of the first column of R_1 .
- Case:
- i) If the data type of the second column of R_1 is a datetime data type, then let E_1 be the value of the second column of R_1 .
 - ii) If the data type of the second column of R_1 is INTERVAL, then let I_1 be the value of the second column of R_1 . Let $E_1 = B_1 + I_1$.
2. If B_1 is the null value or if $E_1 < B_1$, then let $S_1 = E_1$ and let $T_1 = B_1$. Otherwise, let $S_1 = B_1$ and let $T_1 = E_1$.
3. Case:
- (a) If the data type of PD_2 is DATE, TIME, or TIMESTAMP, then let B_2 and E_2 both be the value of PD_2 .
 - (b) If the data type of PD_2 is PERIOD, then let B_2 be the value of BEGIN(PD_2) and E_2 be the value of END(PD_2).
 - (c) Otherwise, let R_2 be the value of <row value expression 2> and let B_2 be the value of the first column of R_2 .
- Case:
- i) If the data type of the second column of R_2 is a datetime data type, then let E_2 be the value of the second column of R_2 .
 - ii) If the data type of the second column of R_2 is INTERVAL, then let I_2 be the value of the second column of R_2 . Let $E_2 = B_2 + I_2$.
4. If B_2 is the null value or if $E_2 < B_2$, then let $S_2 = E_2$ and let $T_2 = B_2$. Otherwise, let $S_2 = B_2$ and let $T_2 = E_2$.
5. The value of the <meets predicate> is the result of the following expression:
- $$T_1 + \text{TIMESTAMP } 10^{-P} = S_2 \text{ OR } T_2 + \text{TIMESTAMP } 10^{-P} = S_1$$