

Package ‘ChIPseqR’

April 9, 2015

Type Package

Title Identifying Protein Binding Sites in High-Throughput Sequencing Data

Version 1.20.0

Date 2012-12-11

Author Peter Humburg

Maintainer Peter Humburg <peter.humburg@well.ox.ac.uk>

Depends R (>= 2.10.0), methods, BiocGenerics, S4Vectors, ShortRead

Imports Biostrings, fBasics, GenomicRanges, graphics, grDevices, HilbertVis, IRanges, methods, ShortRead, stats, timsac, utils

Description ChIPseqR identifies protein binding sites from ChIP-seq and nucleosome positioning experiments. The model used to describe binding events was developed to locate nucleosomes but should be flexible enough to handle other types of experiments as well.

License GPL (>= 2)

LazyLoad yes

Collate classes.R generics.R initialize.R methods.R access.R package.R

biocViews ChIPSeq, Infrastructure

R topics documented:

ChIPseqR-package	2
accessors	3
alignFeature	4
BindScore-class	5
callBindingSites-methods	9
compress-BindScore	12
compress-methods	13
compress-ReadCounts	13
decompress	14
decompress-methods	15

exportBindSequence	15
getBindCor	16
getBindLen	17
getCutoff	18
pickPeak	19
plot,ReadCounts,missing-method	20
plot-BindScore	21
pos2gff	21
ReadCounts-class	22
RLEBindScore-class	24
RLEReadCounts-class	26
simpleNucCall	27
startScore	28
strandPileup	29
windowCounts	31

Index 33

ChIPseqR-package	<i>Identifying Protein Binding Sites in High-Throughput Sequencing Data</i>
------------------	---

Description

ChIPseqR provides a set of functions for the analysis of ChIP-seq data. Protein binding sites are located by identifying a characteristic pattern of peaks in read counts on both DNA strands.

Details

Package:	ChIPseqR
Type:	Package
Version:	1.13.1
Date:	2012-12-11
License:	GPL (>=2)
LazyLoad:	yes

The easiest way to obtain binding site predictions for nucleosomes is to use [simpleNucCall](#). This provides a simple interface to [callBindingSites](#). This function operates on [AlignedRead](#) objects and provides useful defaults for nucleosome analysis. Parameters can be adjusted to detect the presence of other DNA binding proteins, e.g. transcription factors. If more fine control is desired the following steps will produce binding site predictions:

[strandPileup](#): Turn mapped reads into read counts along the genome.

[startScore](#): Score potential binding sites.

[getCutoff](#): Determine cutoff required to achieve desired false discovery rate.

[pickPeak](#): Find all peaks in the binding site score that exceed the significance threshold determined by `getCutoff`. These are the predicted binding sites.

Author(s)

Peter Humburg

Maintainer: Peter Humburg <Peter.Humburg@well.ox.ac.uk>

References

Humburg, P., Helliwell, C., Bulger, D. & Stone, G. ChIPseqR: Analysis of ChIP-seq Experiments. BMC Bioinformatics 12, 39+ (2011).

See Also

[ShortRead](#)

Examples

```
## See simpleNucCall for examples of how to obtain nucleosome predictions.
```

accessors

Access slots of S4 classes

Description

Accessor functions for S4 classes in package "ChIPseqR".

Usage

```
## S4 method for signature ANY
binding(x, ...)
## S4 method for signature ANY
cutoff(x, ...)
## S4 replacement method for signature ANY
cutoff(x, ...) <- value
## S4 method for signature ANY
nullDist(x, ...)
## S4 replacement method for signature ANY
nullDist(x, ...) <- value
## S4 method for signature ANY
peaks(x, ...)
## S4 method for signature ANY
pvalue(x, ...)
## S4 method for signature ANY
support(x, ...)
```

Arguments

x	An S4 object.
...	Further arguments, ignored by default method.
value	New value for slot.

Details

These methods allow safe read (and in some cases write) access to slots of S4 classes and should be used for this purpose rather than modifying slots manually.

Value

The current value of the interrogated slot.

Methods

x = "ANY" Default method for accessor function.

Note

This page documents the generics and their default behaviour. See the help page of each class for class specific implementations.

Author(s)

Peter Humburg

See Also

[ReadCounts](#), [BindScore](#)

alignFeature

Read counts relative to annotated features

Description

Creates a set of (strand specific) read counts centred at the genomic features provided.

Usage

```
alignFeature(data, anno, offset = 1000)
```

Arguments

data	List with read counts as returned by strandPileup .
anno	Data frame with annotation data in GFF format.
offset	Half width of window around start point of annotated features.

Value

List with one component for each feature in anno.

Author(s)

Peter Humburg

References

The GFF file format specification: http://www.sanger.ac.uk/Software/formats/GFF/GFF_Spec.shtml

Examples

```
set.seed(1)

## determine binding site locations
b <- sample(1:8.5e5, 500)

## sample read locations
fwd <- unlist(lapply(b, function(x) sample((x-83):(x-73), 20, replace=TRUE)))
rev <- unlist(lapply(b, function(x) sample((x+73):(x+83), 20, replace=TRUE)))

## add some background noise
fwd <- c(fwd, sample(1:(1e6-25), 5000))
rev <- c(rev, sample(25:1e6, 5000))

## create data.frame with read positions as input to strandPileup
reads <- data.frame(chromosome="chr1", position=c(fwd, rev),
length=25, strand=factor(rep(c("+", "-"), times=c(15000, 15000))))

## create object of class ReadCounts
readPile <- strandPileup(reads, chrLen=1e6, extend=1, plot=FALSE)

## convert binding site locations into GFF format
gff <- data.frame(chromosome="chr1", source="test", feature="binding", start=b-73, end=b+73,
score=".", strand=".", frame=".")

## align read counts relative to binding site location
aligned <- alignFeature(readPile, gff, offset=500)
```

BindScore-class

Class "BindScore"

Description

This class provides the infrastructure to store results of ChIP-seq analysis.

Usage

```

## S4 method for signature BindScore
binding(x)
## S4 method for signature BindScore
chrLength(x, subset)
## S4 method for signature BindScore
cutoff(x, type=c("score", "pvalue"))
## S4 replacement method for signature BindScore
cutoff(x, type=c("score", "pvalue")) <- value
## S4 method for signature BindScore
head(x, n=6, by=c("score", "position"), ...)
## S4 method for signature BindScore
lapply(X, FUN, ...)
## S4 method for signature BindScore
length(x)
## S4 replacement method for signature BindScore
length(x) <- value
## S4 method for signature BindScore
max(x, ..., na.rm=TRUE)
## S4 method for signature BindScore
min(x, ..., na.rm=TRUE)
## S4 method for signature BindScore
names(x)
## S4 replacement method for signature BindScore,ANY
names(x) <- value
## S4 method for signature BindScore
nullDist(x)
## S4 replacement method for signature BindScore
nullDist(x) <- value
## S4 method for signature BindScore
peaks(x, ...)
## S4 method for signature BindScore
range(x, ..., na.rm=TRUE)
## S4 method for signature BindScore
score(x)
## S4 method for signature BindScore
support(x)
## S4 method for signature BindScore
tail(x, n=6, by=c("score", "position"), ...)
BindScore(call, score=list(), pvalue=list(), peaks=list(), cutoff=c(-Inf, 1), nullDist=c(0, 1), names=

```

Arguments

x	Object of class BindScore.
X	Object of class BindScore.
subset	Index vector indicating a subset of x. If subset is missing everything is selected.
type	A string indicating which type of cut-off should be returned or changed. Either "score" or "pvalue"

n	Number of entries to show.
by	A string indicating whether the output should be sorted by score or by position in the genome.
na.rm	Logical indication whether NAs should be ignored.
FUN	Function to apply to results for each chromosome.
value	Replacement value.
call	Function call used to generate the values of the other slots.
score	List of binding site scores. One component per chromosome.
pvalue	List of binding site p-values. One component per chromosome.
peaks	List of significant peaks in binding site score. One component per chromosome.
cutoff	Numeric vector of length two indicating the significance cut-off in terms of score and p-value.
nullDist	Parameters of the null distribution.
names	Character vector providing names for chromosomes.
start	Integer indicating position of first binding site score.
compress	Logical indicating whether scores and p-values should be compressed.
digits	The number of decimal places to retain for compression.
...	Further arguments.

Objects from the Class

Objects can be created by calls of the form `new("BindScore", functionCall, score, pvalue, peaks, cutoff, nullDist)`. Objects of this class are typically created (and returned) by functions that perform peak calling on ChIP-seq data. Usually there should be no need to create them directly.

Slots

functionCall: Object of class "call" storing the function call used to initiate the analysis.

score: Object of class "list". The binding site score. One numeric vector per chromosome.

pvalue: Object of class "list". The (adjusted) p-values corresponding to the scores in slot score.

peaks: Object of class "list" giving the location of significant peaks in the binding site score. These correspond to the location of predicted binding sites.

cutoff: Object of class "numeric" with entries 'pvalue' and 'score' giving the significance threshold used for peak calling in terms of p-value and score.

nullDist: Object of class "numeric" providing the parameters of the null distribution used to determine p-values.

start: Object of class "integer" indicating the index corresponding to the first entry in score (assumed to be the same for all chromosomes).

Methods

- as.data.frame** signature(x = "BindScore"): Convert results into a data.frame giving the location, score and p-value of significant peaks.
- [signature(x = "BindScore", i = "ANY", j = "missing", drop = "missing"): Restrict results to a subset of chromosomes. Chromosomes can either be identified by name or by numerical index.
- [[signature(x = "BindScore", i = "ANY", j = "missing"): Restrict results to a single chromosome. Note that x[["chr1"]] is identical to x["chr1"].
- [[signature(x = "BindScore", i = "ANY", j = "numeric"): subset results to restrict them to a region on a single chromosome.
- binding** signature(x = "BindScore"): Returns length of binding site used during analysis.
- chrLength** signature(x = "BindScore", subset = "ANY"): Returns length of all chromosomes represented in x.
- cutoff<-** signature(x = "BindScore"): Sets the significance cut-off. Argument type=c("score", "pvalue") determines which cut-off is to be set, the other is adjusted accordingly. This recalculates the significance of peaks in the binding site score and may be slow.
- cutoff** signature(x = "BindScore"): Returns significance threshold used for analysis.
- head** signature(x = "BindScore"): Returns the first n peaks. Argument by = c("score", "position") determines whether results are sorted by score or by genomic location.
- lapply** signature(X = "BindScore"): Applies a function to results for each chromosome.
- length<-** signature(x = "BindScore"): Reduces the number of chromosomes for which results are stored, i.e., length(x) <- 3 only retains the first three chromosomes.
- length** signature(x = "BindScore"): Returns the number of binding sites identified by the analysis.
- max** signature(x = "BindScore"): Returns maximum score.
- min** signature(x = "BindScore"): Returns minimum score.
- names<-** signature(x = "BindScore", value = "ANY"): Sets the chromosome names.
- names** signature(x = "BindScore"): Returns the chromosome names.
- nullDist<-** signature(x = "BindScore"): Sets the parameters of the null distribution adjusting the significance cut-off in the process and predicts binding sites using the new null distribution.
- peaks** signature(x = "BindScore"): Returns list of predicted binding sites.
- range** signature(x = "BindScore"): Range of binding site scores.
- score** signature(x = "BindScore"): Returns list of binding site scores.
- support** signature(x = "BindScore"): Returns length of support region used during analysis.
- tail** signature(x = "BindScore"): Returns the last n peaks. Argument by = c("score", "position") determines whether results are sorted by score or by genomic location.

Author(s)

Peter Humburg

References

~put references to the literature/web site here ~

See Also

[ReadCounts](#) for the data structure used as input for the analysis and [callBindingSites](#)

Examples

```
showClass("BindScore")

set.seed(1)

## determine binding site locations
b <- sample(1:1e6, 5000)

## sample read locations
fwd <- unlist(lapply(b, function(x) sample((x-83):(x-73), 20, replace=TRUE)))
rev <- unlist(lapply(b, function(x) sample((x+73):(x+83), 20, replace=TRUE)))

## add some background noise
fwd <- c(fwd, sample(1:(1e6-25), 50000))
rev <- c(rev, sample(25:1e6, 50000))

## create data.frame with read positions as input to strandPileup
reads <- data.frame(chromosome="chr1", position=c(fwd, rev),
length=25, strand=factor(rep(c("+", "-"), times=c(150000, 150000))))

## create object of class ReadCounts
readPile <- strandPileup(reads, chrLen=1e6, extend=1, plot=FALSE)

## predict binding site locations
## the artificial dataset is very small so predictions may not be very reliable
bindScore <- simpleNucCall(readPile, bind=147, support=20, plot=FALSE, compress=FALSE)

## number of binding sites found
length(bindScore)

## the first few predictions, by score
head(bindScore)

## score and p-value cut-off used
cutoff(bindScore)
```

Description

Methods for function `callBindingSites` in Package ‘ChIPseqR’. These methods are used to identify protein binding sites from ChIP-seq data.

Usage

```
## S4 method for signature ANY
callBindingSites(data, chrLen, plot=TRUE, verbose=TRUE, ..., plotTo)
## S4 method for signature character
callBindingSites(data, type, minQual=70, ...)
## S4 method for signature matrix
callBindingSites(data, chrName="chr", ...)
## S4 method for signature ReadCounts
callBindingSites(data, bind, support, background, bgCutoff=0.9, supCutoff=0.9,
fdr = 0.05, extend=1, tailCut=0.95, piLambda=0.5, adapt=FALSE, corSummary=median, compress = TRUE,
digits = 16, plot=TRUE, verbose=TRUE, ask=FALSE, plotTo, ...)
```

Arguments

<code>data</code>	Either an object containing information about mapped reads or a list. See below for details.
<code>bind</code>	Length of binding region to use (see Details).
<code>support</code>	Length of support region to use (see Details).
<code>background</code>	Length of background window. If this is missing it will be set to $10 * (\text{bind} + 2 * \text{support})$.
<code>chrLen</code>	Numeric vector indicating the length of all chromosomes. Only needed when <code>data</code> is an <code>AlignedRead</code> object. <code>readBfaToc</code> may be used to supply this information.
<code>bgCutoff</code>	Numeric value between 0.5 and 1. This determines how much estimates of the background read density are allowed to vary for adjacent windows. Set to 1 to disable cutoff.
<code>supCutoff</code>	Numeric value between 0.5 and 1. This determines how much estimates of the support region read density are allowed to vary for forward and reverse strand. Set to 1 to disable cutoff.
<code>fdr</code>	Target false discovery rate.
<code>extend</code>	Numeric value indicating how far mapped reads should be extended when calculating read counts.
<code>type</code>	Format of alignment file (see <code>readAligned</code> for details).
<code>minQual</code>	Minimum alignment quality to use. All reads with lower alignment quality are discarded.
<code>tailCut</code>	Truncation point used to exclude outliers when estimating null distribution.
<code>chrName</code>	Name to use for the single chromosome.
<code>piLambda</code>	If <code>adapt=TRUE</code> this parameter is used to estimate the proportion of scores not related to binding sites.

adapt	Logical indicating whether an adaptive false discovery rate should be used. If this is FALSE (the default) the usual Benjamini-Hochberg procedure is used to control the FDR.
corSummary	Function used to summarise cross-correlation across chromosomes. See the Details section on binding and support region.
compress	Logical indicating whether the return value should be compressed.
digits	Number of decimal places to retain for binding site score for compression.
plot	Logical. If plot=TRUE (the default) some diagnostic plots are produced during the analysis.
verbose	Logical. If verbose=TRUE (the default) status messages are printed to indicate progress.
ask	Logical. Setting this to TRUE causes the system to wait for user input before displaying a new plot. See devAskNewPage .
plotTo	Character string giving the name of a file that should be used to store plots generated during the analysis. If this is not missing a pdf file with the given name will be created.
...	Additional arguments. Most methods pass them on to the ReadCounts method.

Details

The length of binding and support regions can either be given as a single value or as a range of possible values (by providing the minimum and maximum). In the latter case the cross-correlation between read counts on forward and reverse strand will be used to determine a value within that range. Note that this may lead sub-optimal choices of binding and support region length.

Value

An object of class [BindScore](#) if `compress = FALSE`, otherwise an object of class [RLEBindScore](#)

Methods

data = "ANY" Default method to handle all forms of input not explicitly handled by their own method. In particular this will be used for objects of class [AlignedRead](#) and `data.frame` but it will handle class for which a [strandPileup](#) method is available.

data = "character" Allows to use a file name referring to a file of mapped sequence reads as input.

data = "matrix" Uses a matrix of read counts (for a single chromosome) as input.

data = "ReadCounts" This methods implements the peak calling algorithm. Other methods will typically reformat their input and pass it on to this method.

See Also

[simpleNucCall](#) for an interface with nucleosome specific defaults. This function uses [strandPileup](#), [startScore](#), [getCutoff](#) and [pickPeak](#). See the help pages of these functions for additional detail on the individual steps involved. See [getBindLen](#) for details on the estimation of binding and support region length.

Examples

```

set.seed(1)

## determine binding site locations
b <- sample(1:1e6, 5000)

## sample read locations
fwd <- unlist(lapply(b, function(x) sample((x-83):(x-73), 20, replace=TRUE)))
rev <- unlist(lapply(b, function(x) sample((x+73):(x+83), 20, replace=TRUE)))

## add some background noise
fwd <- c(fwd, sample(1:(1e6-25), 50000))
rev <- c(rev, sample(25:1e6, 50000))

## create data.frame with read positions as input to strandPileup
reads <- data.frame(chromosome="chr1", position=c(fwd, rev),
length=25, strand=factor(rep(c("+", "-"), times=c(150000, 150000))))

## create object of class ReadCounts
readPile <- strandPileup(reads, chrLen=1e6, extend=1, plot=FALSE)

## predict binding site locations
## the artificial dataset is very small so predictions may not be very reliable
bindScore <- callBindingSites(readPile, bind=147, support=20, background=2000, plot=FALSE)

```

compress-BindScore *Compress BindScore Objects*

Description

Generates a compressed representation of binding site scores.

Usage

```

## S4 method for signature BindScore
compress(x, digits=16)

```

Arguments

x	An object of class <code>BindScore</code> .
digits	Integer indicating the number of decimal places to retain.

Details

Binding site scores are compressed by first rounding them to `digits` decimal places and then applying run-length encoding.

Value

An object of class [RLEBindScore](#).

Note

Compression reduces the precision of binding site scores and may affect results, especially for small values of digits.

Author(s)

Peter Humburg

See Also

[Rle](#), [RleList](#), [compress-BindScore](#)

compress-methods *Methods for Function compress in Package 'ChIPseqR'*

Description

Methods to obtain compressed versions of data structures.

Methods

`signature(x = "BindScore")` Converts x into an object of class [RLEBindScore](#).
`signature(x = "ReadCounts")` Converts x into an object of class [RLEReadCounts](#).
`signature(x = "RLEBindScore")` Returns (the already compressed) x.
`signature(x = "RLEReadCounts")` Returns (the already compressed) x.

compress-ReadCounts *Compress ReadCount Objects*

Description

Generates a compressed representation of read counts.

Usage

```
## S4 method for signature ReadCounts  
compress(x)
```

Arguments

x An object of class [ReadCounts](#)

Details

Run-length encoding is used to obtain a compressed representation of read counts.

Value

An object of class [RLEReadCounts](#)

Author(s)

Peter Humburg

See Also

[Rle](#), [RleList](#), [compress-BindScore](#)

decompress

Extract Read Count and Binding Site Score Representations

Description

These methods extract read count and binding site scores from compressed representations.

Usage

```
## S4 method for signature RLEReadCounts  
decompress(x)  
## S4 method for signature RLEBindScore  
decompress(x)
```

Arguments

x An object of class [RLEBindScore](#) or [RLEReadCounts](#).

Value

An object of class [BindScore](#) or [ReadCounts](#) respectively.

Author(s)

Peter Humburg

See Also

[compress](#)

decompress-methods *Methods for Function decompress in Package 'ChIPseqR'*

Description

Methods to extract compressed data structures.

Methods

signature(x = "ANY") The default method simply returns x.
signature(x = "Rle") Restores the atomic vector encoded in x.
signature(x = "RLEBindScore") Returns an object of [BindScore](#).
signature(x = "RleList") Extracts the components of x and restores them to atomic vectors.
signature(x = "RLEReadCounts") Returns an object of [ReadCounts](#).

exportBindSequence *Export sequence of predicted binding sites*

Description

Extracts sequence of predicted binding sites from reference genome and exports them in FASTA format.

Usage

```
exportBindSequence(prediction, reference, bind, overlap = FALSE, file = "")
```

Arguments

prediction	Object of class BindScore .
reference	Reference genome sequence (as XStringSet object).
bind	Length of binding site to assume for sequence extraction. This may be missing in which case the value is derived from prediction.
overlap	Logical indicating whether overlapping predictions should be allowed.
file	Name of output file.

Value

An [XStringViews](#) object containing the sequences. If a file name is provided this is returned invisibly.

Author(s)

Peter Humburg

References

Package Biostrings

See Also

[XStringViews](#), [XStringSet](#), [BindScore](#)

getBindCor

Calculate cross-correlation between read counts

Description

This function calculates the cross-correlation between read counts on forward and reverse strand.

Usage

```
getBindCor(data, max.lag, summary, plot = TRUE, ...)
```

Arguments

data	An object of class ReadCounts
max.lag	Maximum lag to use in cross-correlation calculation.
summary	Function to use to summarise cross-correlation across chromosomes.
plot	Logical indicating whether to plot cross-correlation.
...	Further arguments, currently ignored.

Details

Function [fttcor](#) in package “timsac” is used to carry out the computation.

Value

The (summarised) cross-correlation. If `summary` is missing a list of cross-correlations for each chromosome is returned.

Author(s)

Peter Humberg

See Also

[fttcor](#), [ReadCounts](#), [getBindLen](#)

`getBindLen`*Estimate length of binding and support region*

Description

The cross-correlation between forward and reverse strand read counts is used to estimate the distance between peaks on both strands. This is then used to derive suitable values for the length of binding and support regions.

Usage

```
getBindLen(data, bind, support, summary = median, verbose = FALSE, plot = TRUE, ...)
```

Arguments

<code>data</code>	An object of class ReadCounts .
<code>bind</code>	Either known length of binding region or minimum and maximum of binding region length to consider.
<code>support</code>	Either known length of support region or minimum and maximum of support region length to consider.
<code>summary</code>	Function to use to summarise cross-correlation across chromosomes.
<code>verbose</code>	Logical indicating whether progress messages should be printed.
<code>plot</code>	Logical indicating whether cross-correlation should be plotted.
<code>...</code>	Further arguments to getBindCor .

Details

This assumes that the first peak in cross-correlation corresponds to the length of the binding site. Note that this is not accurate. The peak is closer to $\text{bind} + 2 * m$ where m is the median of the read distribution in the support region ('read distribution in the support region' means the read density as a function of distance to binding site start/end). Consequently this method will overestimate the length of the binding site. If either `bind` or `support` are of length 1 this is assumed to be the known value and a more accurate estimate for the remaining parameter is used.

Value

A numeric vector giving the estimated lengths of binding and support regions.

Author(s)

Peter Humburg

`getCutoff`*Determine significance threshold for binding site scores*

Description

Given a vector of observed binding site scores and a desired false discovery rate, this function returns the lowest score that should be considered significant to achieve the given false discovery rate.

Usage

```
getCutoff(score, alpha = 0.05, tailCut = 0.95, adapt = FALSE, lambda, plot = TRUE, returnPval = TRUE)
```

Arguments

<code>score</code>	Numeric vector with binding site scores.
<code>alpha</code>	Desired false discovery rate.
<code>tailCut</code>	Truncation point used to exclude outliers when fitting the null distribution.
<code>adapt</code>	Logical indicating whether an adaptive false discovery rate should be used.
<code>lambda</code>	If <code>adapt</code> is TRUE this is used in estimating the proportion of scores that is unrelated to binding sites.
<code>plot</code>	If this is TRUE (the default) a plot of the observed score distribution and estimated null distribution is generated.
<code>returnPval</code>	Indicates whether or not the corrected p-values for all scores should be returned.

Value

A list with components

<code>cutoff</code>	A numeric vector with the score and nominal false discovery rate corresponding to the determined cutoff.
<code>h0</code>	A numeric vector with the mean and standard deviation of the estimated null distribution.
<code>pvalue</code>	If <code>returnPval</code> is TRUE, the p-values corresponding to the scores in <code>score</code> . Note that all missing values are removed.
<code>pi0</code>	If <code>adapt</code> is TRUE, the estimated proportion of scores not related to binding sites.

Note

This function is used by `callBindingSites` to determine the significance threshold for peak-calling.

Author(s)

Peter Humburg

References

For the adaptive false discovery rate procedure used if `adapt=TRUE` see JD Storey, JE Taylor and D Siegmund. Strong control, conservative point estimation and simultaneous conservative consistency of false discovery rates: a unified approach. *Journal of the Royal Statistical Society B*, 66(1):187-205, 2004.

See Also

[callBindingSites](#)

pickPeak	<i>Identify peaks above a given threshold</i>
----------	---

Description

Given a vector of scores and a threshold, this function finds all peaks that exceed the threshold.

Usage

```
pickPeak(score, threshold, offset = 0, sub = FALSE)
```

Arguments

score	Numeric vector.
threshold	All values in score below this value are ignored.
offset	Offset to add to the determined peak locations.
sub	Logical. If this is FALSE (the default) for each region that exceeds the threshold only the global maximum is returned. Otherwise local maxima are returned as well.

Value

If `sub = FALSE` a numeric vector giving the location of all peaks. Otherwise a list with components

peaks	The same peak locations that are returned for <code>sub = FALSE</code> .
subPeaks	A list with one component for each entry in 'peaks' giving the location of local maxima.

Note

This function is used by [callBindingSites](#) for peak-calling.

Author(s)

Peter Humburg

See Also

[callBindingSites](#), [startScore](#), [getCutoff](#)

plot,ReadCounts,missing-method

Diagnostic Plots for Read Counts

Description

Produces plots to assess the distribution of reads, either for an entire chromosome or within a (small) window.

Usage

```
## S4 method for signature ReadCounts,missing
plot(x, chr, center, score, width=2000, type=c("hilbert", "window"), ...)
## S4 method for signature RLEReadCounts,missing
plot(x, chr, center, score, width=2000, type=c("hilbert", "window"), ...)
```

Arguments

x	Object of class ReadCounts or RLEReadCounts .
chr	Index or name of chromosome for which read counts should be plotted.
center	For type 'window', the center coordinate of the window to plot.
score	For type 'window', an object of type BindScore (or BindScore) that should be used to include information about the score and predicted binding sites into the plot.
width	For type 'window', the width of the window.
type	Character string indicating the type of plot that should be produced (see details).
...	Further arguments (see details).

Details

Type 'window' produces a plot that shows read counts as vertical bars. If score is not missing, it is used to plot the score and predicted binding sites (if any) as well. Any additional arguments are passed on to [.plotWindow](#).

Type 'hilbert' produces a Hilbert curve plot of read counts for an entire chromosome. Additional arguments are passed on to [.plotReads](#).

Value

Called for its side effect.

Author(s)

Peter Humburg

See Also

[hilbertImage](#)

plot-BindScore *Diagnostic Plots for Binding Site Scores*

Description

Generates plots to assess the fit of the estimated null distribution.

Usage

```
## S4 method for signature BindScore,missing  
plot(x, npoints = 10000, type=c("density", "qqplot"), ...)
```

Arguments

x	An object of class BindScore .
npoints	Maximum number of points to plot in a QQ-plot.
type	Character string indicating the plot type.
...	Further arguments (currently ignored).

Details

Type ‘density’ produces a histogram of binding site scores with overlaid null distribution. Type ‘qqplot’ produces a normal QQ-plot comparing the observed binding site scores to the null distribution.

Value

Called for its side effect.

Author(s)

Peter Humburg

pos2gff *Convert genome coordinates into GFF format*

Description

Provides facility to export the location of genomic features to a GFF formatted file.

Usage

```
pos2gff(pos, method, feature, len, strand, score, name)
```

Arguments

pos	Named list with one component per chromosome giving the start position of features on that chromosome.
method	Entry for method field in GFF file. Recycled as necessary
feature	Entry for feature field in GFF file. Recycled as necessary
len	Length of fetures. This is used to calculate matching end positions for each start position given in pos
strand	Entry for feature field in GFF file. Recycled as necessary
score	Entry for feature field in GFF file. Recycled as necessary
name	Entry for feature field in GFF file. Recycled as necessary

Value

A data.frame with columns chromosome, method, feature, start, end, score, strand. Writing this data frame to a text file produces a GFF formatted file.

Author(s)

Peter Humburg

References

The GFF specification: http://www.sanger.ac.uk/Software/formats/GFF/GFF_Spec.shtml

Examples

```
pos <- list(chr1=c(10, 50, 60), chr2=c(22, 200, 500))
pos2gff(pos, "test", "foo", 25, c("+", "+", "-", "+", "-", "-"), 0, "test")
```

ReadCounts-class *Class "ReadCounts"*

Description

Represents counts of (possibly extended) reads for each strand of the genome.

Usage

```
ReadCounts(counts=list(), names=NULL, compress=TRUE)
```

Arguments

counts	A list of read counts. Each component is a two column matrix of strand specific read counts for a chromosome.
names	Character vector of chromosome names. If this is NULL the names of counts are used instead.
compress	Logical indicating whether read counts should be compressed.

Objects from the Class

Objects can be created by calls of the form `ReadCounts(counts, names, compress=FALSE)` or by calls to [strandPileup](#).

Slots

`counts`: Object of class "list" with one component per chromosome, containing a matrix of read counts (one column per strand).

Methods

`[<- signature(x = "ReadCounts", i = "ANY", j = "missing")`: Replace read counts for chromosomes indicated by `i`.

`[signature(x = "ReadCounts", i = "ANY", j = "missing", drop = "missing")`: Returns list of read counts for chromosomes indicated by `i`.

`[[<- signature(x = "ReadCounts", i = "ANY", j = "missing")`: Replace read counts for chromosome `i`.

`[[signature(x = "ReadCounts", i = "ANY", j = "missing")`: Returns read counts for chromosome `i`.

`$<- signature(x = "ReadCounts")`: Replace read counts for chromosome `i` (by name).

`$ signature(x = "ReadCounts")`: Returns read counts for chromosome `i` (by name).

`callBindingSites signature(data = "ReadCounts")`: Predict bindingsites from read counts.

`chrLength signature(x = "ReadCounts", subset = "ANY")`: Returns length of all chromosomes represented in `x`.

`lapply signature(X = "ReadCounts")`: Apply function to read counts for each chromosome.

`length<- signature(x = "ReadCounts")`: Change the number of chromosomes represented by `x` to value.

`length signature(x = "ReadCounts")`: Number of chromosomes represented by `x`.

`names<- signature(x = "ReadCounts", value = "ANY")`: Change names of chromosomes.

`names signature(x = "ReadCounts")`: Chromosome names.

`nreads signature(x = "ReadCounts", byStrand = "Logical", subset = "ANY")`: Returns the number of reads on each chromosome, split by strand (if `byStrand` is TRUE).

`sapply signature(X = "ReadCounts")`: Apply function to read counts for each chromosome.

Author(s)

Peter Humburg

See Also

[BindScore](#), [strandPileup](#), [compress](#), [decompress](#)

Examples

```

showClass("ReadCounts")

## generate some very simple artificial read data
set.seed(1)
fwd <- sample(c(50:70, 250:270), 30, replace=TRUE)
rev <- sample(c(197:217, 347:417), 30, replace=TRUE)
## create data.frame with read positions as input to strandPileup
reads <- data.frame(chromosome="chr1", position=c(fwd, rev),
length=25, strand=factor(rep(c("+", "-"), times=c(30, 30))))

## create object of class ReadCounts
readPile <- strandPileup(reads, chrLen=500, extend=1, plot=FALSE, compress=FALSE)

names(readPile)
length(readPile)
sapply(readPile, sum)

```

RLEBindScore-class *Run-length Encoded Binding Site Scores*

Description

This class provides a memory efficient representation of binding site scores.

Objects from the Class

Objects can be created by calls of the form `BindScore(functionCall, score, pvalue, peaks, cutoff, nullDist, name)` or through calls to [callBindingSites](#).

Slots

functionCall: Object of class "call" storing the function call used to initiate the analysis.

score: Object of class "list". The binding site score. One run-length encoded numeric vector per chromosome.

pvalue: Object of class "list". The (adjusted and run-length encoded) p-values corresponding to the scores in slot score.

peaks: Object of class "list" giving the location of significant peaks in the binding site score. These correspond to the location of predicted binding sites.

cutoff: Object of class "numeric" with entries 'pvalue' and 'score' giving the significance threshold used for peak calling in terms of p-value and score.

nullDist: Object of class "numeric" providing the parameters of the null distribution used to determine p-values.

start: Object of class "integer" indicating the index corresponding to the first entry in score (assumed to be the same for all chromosomes).

Extends

Class "[BindScore](#)", directly.

Methods

decompress signature(x = "RLEBindScore"): conversion to [BindScore](#) object.

Author(s)

Peter Humburg

See Also

[BindScore](#), [Rle](#)

Examples

```
showClass("RLEBindScore")

set.seed(1)

## determine binding site locations
b <- sample(1:1e6, 5000)

## sample read locations
fwd <- unlist(lapply(b, function(x) sample((x-83):(x-73), 20, replace=TRUE)))
rev <- unlist(lapply(b, function(x) sample((x+73):(x+83), 20, replace=TRUE)))

## add some background noise
fwd <- c(fwd, sample(1:(1e6-25), 50000))
rev <- c(rev, sample(25:1e6, 50000))

## create data.frame with read positions as input to strandPileup
reads <- data.frame(chromosome="chr1", position=c(fwd, rev),
length=25, strand=factor(rep(c("+", "-"), times=c(150000, 150000))))

## create object of class ReadCounts
readPile <- strandPileup(reads, chrLen=1e6, extend=1, plot=FALSE)

## predict binding site locations
## the artificial dataset is very small so predictions may not be very reliable
bindScore <- simpleNucCall(readPile, bind=147, support=20, plot=FALSE, compress=TRUE)

## number of binding sites found
length(bindScore)

## the first few predictions, by score
head(bindScore)

## score and p-value cut-off used
cutoff(bindScore)
```

RLEReadCounts-class *Run-length Encoded Read Counts*

Description

This class provides a memory efficient representation of strand specific read counts.

Objects from the Class

Objects can be created by calls of the form `ReadCounts(counts, names, compress = TRUE)` or by calls to `strandPileup`.

Slots

`counts`: Object of class "list" with one component per chromosome, containing a read counts encoded in an object of class `RleList`.

Extends

Class "`ReadCounts`", directly.

Methods

chrLength signature(x = "RLEReadCounts"): Returns length of all chromosomes represented in x.

decompress signature(x = "RLEReadCounts"): Expands read counts and returns object of class `ReadCounts`.

nreads signature(x = "RLEReadCounts"): Returns the number of reads on each chromosome, split by strand (if `byStrand` is TRUE)

plot signature(x = "RLEReadCounts", y = "missing"): Generates plots of read counts.

Author(s)

Peter Humburg

See Also

`ReadCounts`, `RleList`

Examples

```
showClass("RLEReadCounts")

## generate some very simple artificial read data
set.seed(1)
fwd <- sample(c(50:70, 250:270), 30, replace=TRUE)
rev <- sample(c(197:217, 347:417), 30, replace=TRUE)
## create data.frame with read positions as input to strandPileup
```

```
reads <- data.frame(chromosome="chr1", position=c(fwd, rev),
length=25, strand=factor(rep(c("+", "-"), times=c(30, 30))))

## create object of class ReadCounts
readPile <- strandPileup(reads, chrLen=500, extend=1, plot=FALSE, compress=TRUE)

names(readPile)
length(readPile)
sapply(readPile, sum)
```

simpleNucCall

Predict nucleosome positions from high-throughput sequencing data

Description

This function provides a simplified interface to [callBindingSites](#) with defaults suitable for the detection of nucleosomes.

Usage

```
simpleNucCall(data, bind=128, support=17, background=2000, chrLen, ...)
```

Arguments

data	Either an object of class AlignedRead or a list. See below for details.
bind	Length of binding region to use (see Details).
support	Length of support region to use (see Details).
background	Length of background window. If this is missing it will be set to $10 * (\text{bind} + 2 * \text{support})$.
chrLen	Numeric vector indicating the length of all chromosomes. Only needed when data is an AlignedRead object. readBfaToc may be used to supply this information.
...	Further arguments to callBindingSites

Value

A list with components

binding	A data.frame with columns 'chromosome', 'position', 'score' and 'pvalue' indicating the centre of predicted binding sites together with their score and associated p-value.
score	A list with all calculated scores. One numeric vector per chromosome.
pval	A list with all corrected p-values. One numeric vector per chromosome.

Author(s)

Peter Humburg

References

~put references to the literature/web site here ~

See Also

[callBindingSites](#) for additional parameters.

Examples

```
## generate some simple artificial read data
set.seed(1)

## determine binding site locations
b <- sample(1:1e6, 5000)

## sample read locations
fwd <- unlist(lapply(b, function(x) sample((x-83):(x-73), 20, replace=TRUE)))
rev <- unlist(lapply(b, function(x) sample((x+73):(x+83), 20, replace=TRUE)))

## add some background noise
fwd <- c(fwd, sample(1:(1e6-25), 50000))
rev <- c(rev, sample(25:1e6, 50000))

## create data.frame with read positions as input to strandPileup
reads <- data.frame(chromosome="chr1", position=c(fwd, rev),
length=25, strand=factor(rep(c("+", "-"), times=c(150000, 150000))))

## create object of class ReadCounts
readPile <- strandPileup(reads, chrLen=1e6, extend=1, plot=FALSE)

## predict binding site locations
bindScore <- simpleNucCall(readPile, bind=147, support=20, plot=FALSE)
```

startScore

Score potential protein binding sites

Description

For each position in the genome this function computes a score indicating the likelihood that a protein binding site starts at that position.

Usage

```
startScore(data, b, support, background, bgCutoff, supCutoff)
```

Arguments

data	A two column matrix with read counts. The two columns correspond to reads on the forward and reverse strand respectively.
b	Length of binding region.
support	Length of support region.
background	Length of background window.
bgCutoff	Cutoff for the change in read rates between adjacent windows (see Details).
supCutoff	Cutoff for the change in read rates between support regions on forward and reverse strand (see Details).

Details

Robust estimates of read rates in background windows and support regions are obtained by limiting the difference between related estimates. Consider a forward support region of length 10 containing 20 reads. The maximum likelihood estimate for the rate parameter of the (assumed) underlying Poisson distribution is $\hat{\lambda} = \frac{20}{10} = 2$. If there are 50 reads in the reverse support region a robust estimate of the rate parameter is obtained as `max(50/10, qpois(supCutoff, lambda=lambda_hat))`

Value

Numeric vector with binding site scores.

Note

Instead of calling this function directly use [callBindingSites](#).

Author(s)

Peter Humburg

See Also

[callBindingSites](#)

strandPileup

Strand specific read counts

Description

Given a set of aligned reads this function computes the number of reads starting at each position in the genome.

Usage

```
## S4 method for signature AlignedRead
strandPileup(aligned, chrLen, extend, coords=c("leftmost", "fiveprime"),
compress = TRUE, plot = TRUE, ask = FALSE, ...)
## S4 method for signature data.frame
strandPileup(aligned, chrLen, extend, coords=c("leftmost", "fiveprime"),
compress = TRUE, plot = TRUE, ask = FALSE, ...)
```

Arguments

aligned	An object containing information about aligned reads (see Details).
chrLen	A numeric vector giving the length of each chromosome.
extend	A numeric value indicating how far reads should be extended.
coords	A character value indicating the coordinate system to use. See coverage for details.
compress	Logical indicating whether read counts should be compressed.
plot	If this is TRUE (the default) read coverage is plotted for all chromosomes.
ask	Logical. Setting this to TRUE causes the system to wait for user input before displaying a new plot. See devAskNewPage .
...	Further arguments to coverage .

Details

The method for `data.frame` requires the column names to follow a strict naming scheme. Required columns are

‘chromosome’ A factor with chromosome names.

‘strand’ A factor with levels “-” and “+” indicating which strand the read mapped to.

‘start’ or ‘position’ Start position of read on chromosome.

‘end’ or ‘length’ End position of read or length of read respectively.

Value

An object of class [ReadCounts](#).

Author(s)

Peter Humburg

See Also

[coverage](#), [AlignedRead](#), [callBindingSites](#)

Examples

```
## generate some very simple artificial read data
set.seed(1)
fwd <- sample(c(50:70, 250:270), 30, replace=TRUE)
rev <- sample(c(197:217, 347:417), 30, replace=TRUE)
## create data.frame with read positions as input to strandPileup
reads <- data.frame(chromosome="chr1", position=c(fwd, rev),
length=25, strand=factor(rep(c("+", "-"), times=c(30, 30))))

readPile <- strandPileup(reads, chrLen=500, extend=1, plot=FALSE)
```

windowCounts

Summarize read counts in a sliding window

Description

Read counts are summarized in a sliding window of variable size with variable overlap between windows.

Usage

```
windowCounts(reads, window = 1000, shift = 500, method = sum)
```

Arguments

reads	Numeric vector of read counts.
window	Width of window.
shift	Distance between consecutive window start positions.
method	Function used to produce a summary for each window. It should accept a single numeric vector as argument.

Value

If method returns a single value a vector of all window summaries is returned, otherwise the return value is a list with one component for each window.

Author(s)

Peter Humburg

Examples

```
## generate some very simple artificial read data
set.seed(1)
fwd <- sample(c(50:70, 250:270), 30, replace=TRUE)
rev <- sample(c(197:217, 347:417), 30, replace=TRUE)
## create data.frame with read positions as input to strandPileup
reads <- data.frame(chromosome="chr1", position=c(fwd, rev),
length=25, strand=factor(rep(c("+", "-"), times=c(30, 30))))

## create object of class ReadCounts
readPile <- strandPileup(reads, chrLen=501, extend=1, plot=FALSE, compress=FALSE)

## get number of reads in sliding window
wdwCount <- windowCounts(apply(readPile[[1]], 1, sum), window=10, shift=5)
```


Index

- *Topic **classes**
 - BindScore-class, 5
 - ReadCounts-class, 22
 - RLEBindScore-class, 24
 - RLEReadCounts-class, 26
- *Topic **hplot**
 - plot, ReadCounts, missing-method, 20
 - plot-BindScore, 21
- *Topic **htest**
 - callBindingSites-methods, 9
 - getCutoff, 18
 - simpleNucCall, 27
- *Topic **methods**
 - callBindingSites-methods, 9
 - compress-methods, 13
 - decompress-methods, 15
- *Topic **misc**
 - alignFeature, 4
 - pickPeak, 19
 - windowCounts, 31
- *Topic **models**
 - callBindingSites-methods, 9
 - simpleNucCall, 27
 - startScore, 28
- *Topic **package**
 - ChIPseqR-package, 2
- *Topic **utilities**
 - accessors, 3
 - compress-BindScore, 12
 - compress-ReadCounts, 13
 - decompress, 14
 - exportBindSequence, 15
 - getBindCor, 16
 - getBindLen, 17
 - pos2gff, 21
 - strandPileup, 29
 - .plotReads, 20
 - .plotWindow, 20
 - [, BindScore, ANY, missing, missing-method (BindScore-class), 5
 - [, ReadCounts, ANY, missing, missing-method (ReadCounts-class), 22
 - [<-, ReadCounts, ANY, missing, ANY-method (ReadCounts-class), 22
 - [<-, ReadCounts, ANY, missing-method (ReadCounts-class), 22
 - [[, BindScore, ANY, missing-method (BindScore-class), 5
 - [[, BindScore, ANY, numeric-method (BindScore-class), 5
 - [[, ReadCounts, ANY, missing-method (ReadCounts-class), 22
 - [[<-, ReadCounts, ANY, missing, ANY-method (ReadCounts-class), 22
 - [[<-, ReadCounts, ANY, missing-method (ReadCounts-class), 22
 - \$, ReadCounts-method (ReadCounts-class), 22
 - \$<-, ReadCounts, ANY-method (ReadCounts-class), 22
 - \$<-, ReadCounts-method (ReadCounts-class), 22
 - accessors, 3
 - AlignedRead, 2, 10, 11, 27, 30
 - alignFeature, 4
 - as.data.frame, BindScore-method (BindScore-class), 5
 - binding (accessors), 3
 - binding, ANY-method (accessors), 3
 - binding, BindScore-method (BindScore-class), 5
 - binding-methods (accessors), 3
 - BindScore, 4, 11, 12, 14–16, 20, 21, 23, 25
 - BindScore (BindScore-class), 5
 - BindScore-class, 5
 - callBindingSites, 2, 9, 18, 19, 24, 27–30

- callBindingSites
 - (callBindingSites-methods), 9
- callBindingSites, ANY-method
 - (callBindingSites-methods), 9
- callBindingSites, character-method
 - (callBindingSites-methods), 9
- callBindingSites, matrix-method
 - (callBindingSites-methods), 9
- callBindingSites, ReadCounts-method
 - (callBindingSites-methods), 9
- callBindingSites-methods, 9
- ChIPseqR (ChIPseqR-package), 2
- ChIPseqR-package, 2
- chrLength (ReadCounts-class), 22
- chrLength, BindScore-method
 - (BindScore-class), 5
- chrLength, ReadCounts-method
 - (ReadCounts-class), 22
- chrLength, RLEReadCounts-method
 - (RLEReadCounts-class), 26
- compress, 14, 23
- compress (compress-methods), 13
- compress, BindScore-method
 - (compress-BindScore), 12
- compress, ReadCounts-method
 - (compress-ReadCounts), 13
- compress, RLEBindScore-method
 - (compress-methods), 13
- compress, RLEReadCounts-method
 - (compress-methods), 13
- compress-BindScore, 12
- compress-methods, 13
- compress-ReadCounts, 13
- coverage, 30
- cutoff (accessors), 3
- cutoff, ANY-method (accessors), 3
- cutoff, BindScore-method
 - (BindScore-class), 5
- cutoff-methods (accessors), 3
- cutoff<- (accessors), 3
- cutoff<-, ANY-method (accessors), 3
- cutoff<-, BindScore-method
 - (BindScore-class), 5
- cutoff<-methods (accessors), 3
- decompress, 14, 23
- decompress, ANY-method
 - (decompress-methods), 15
- decompress, Rle-method
 - (decompress-methods), 15
- decompress, RLEBindScore-method
 - (decompress), 14
- decompress, RleList-method
 - (decompress-methods), 15
- decompress, RLEReadCounts-method
 - (decompress), 14
- decompress-methods, 15
- devAskNewPage, 11, 30
- exportBindSequence, 15
- fftcor, 16
- fftcor, 16
- getBindCor, 16, 17
- getBindLen, 11, 16, 17
- getCutoff, 2, 11, 18, 19
- head, BindScore-method
 - (BindScore-class), 5
- hilbertImage, 20
- lapply, BindScore-method
 - (BindScore-class), 5
- lapply, ReadCounts-method
 - (ReadCounts-class), 22
- length, BindScore-method
 - (BindScore-class), 5
- length, ReadCounts-method
 - (ReadCounts-class), 22
- length<-, BindScore-method
 - (BindScore-class), 5
- length<-, ReadCounts-method
 - (ReadCounts-class), 22
- max, BindScore-method (BindScore-class), 5
- min, BindScore-method (BindScore-class), 5
- names, BindScore-method
 - (BindScore-class), 5
- names, ReadCounts-method
 - (ReadCounts-class), 22
- names<-, BindScore, ANY-method
 - (BindScore-class), 5
- names<-, ReadCounts, ANY-method
 - (ReadCounts-class), 22

- nreads (ReadCounts-class), 22
- nreads, ReadCounts-method
 - (ReadCounts-class), 22
- nreads, RLEReadCounts-method
 - (RLEReadCounts-class), 26
- nullDist (accessors), 3
- nullDist, ANY-method (accessors), 3
- nullDist, BindScore-method
 - (BindScore-class), 5
- nullDist-methods (accessors), 3
- nullDist<- (accessors), 3
- nullDist<-, ANY-method (accessors), 3
- nullDist<-, BindScore-method
 - (BindScore-class), 5
- nullDist<--methods (accessors), 3
- peaks (accessors), 3
- peaks, ANY-method (accessors), 3
- peaks, BindScore-method
 - (BindScore-class), 5
- peaks-methods (accessors), 3
- pickPeak, 3, 11, 19
- plot, BindScore, missing-method
 - (plot-BindScore), 21
- plot, ReadCounts, missing-method, 20
- plot, RLEReadCounts, missing-method
 - (plot, ReadCounts, missing-method), 20
- plot-BindScore, 21
- pos2gff, 21
- pvalue (accessors), 3
- pvalue, ANY-method (accessors), 3
- pvalue-methods (accessors), 3
- range, BindScore-method
 - (BindScore-class), 5
- readAligned, 10
- readBfaToc, 10, 27
- ReadCounts, 4, 9, 13–17, 20, 26, 30
- ReadCounts (ReadCounts-class), 22
- ReadCounts-class, 22
- Rle, 13, 14, 25
- RLEBindScore, 11, 13, 14
- RLEBindScore-class, 24
- RleList, 13, 14, 26
- RLEReadCounts, 13, 14, 20
- RLEReadCounts-class, 26
- sapply, ReadCounts-method
 - (ReadCounts-class), 22
- score (accessors), 3
- score, BindScore-method
 - (BindScore-class), 5
- ShortRead, 3
- simpleNucCall, 2, 11, 27
- startScore, 2, 11, 19, 28
- strandPileup, 2, 4, 11, 23, 26, 29
- strandPileup, AlignedRead-method
 - (strandPileup), 29
- strandPileup, data.frame-method
 - (strandPileup), 29
- strandPileup-methods (strandPileup), 29
- support (accessors), 3
- support, ANY-method (accessors), 3
- support, BindScore-method
 - (BindScore-class), 5
- support-methods (accessors), 3
- tail, BindScore-method
 - (BindScore-class), 5
- windowCounts, 31
- XStringSet, 15, 16
- XStringViews, 15, 16