

# Package ‘ImmuneSpaceR’

April 14, 2017

**Type** Package

**Title** A Thin Wrapper around the ImmuneSpace Database

**Version** 1.2.0

**Date** 2014-06-12

**Author** Greg Finak, Renan Sauteraud, Mike Jiang, Gil Guday

**Maintainer** Renan Sauteraud <rsautera@fhcrc.org>

**VignetteBuilder** knitr

**Description** Provides a convenient API for accessing data sets within ImmuneSpace ([www.immunospace.org](http://www.immunospace.org)), the data repository and analysis platform of the Human Immunology Project Consortium (HIPC).

**biocViews** DataImport, DataRepresentation, ThirdPartyClient

**URL** <https://github.com/RGLab/ImmuneSpaceR>

**BugReports** <https://github.com/RGLab/ImmuneSpaceR/issues>

**License** GPL-2

**Suggests** knitr, rmarkdown, testthat

**Imports** methods, data.table, RCurl, Rlabkey (>= 2.1.127), Biobase, pheatmap, ggplot2, scales, stats, gtools, gplots, reshape2

**Collate** 'CreateConnection.R' 'ImmuneSpace.R' 'ImmuneSpaceR.R' 'getDataset.R' 'getGEMatrix.R' 'quick\_plot.R' 'utils.R' 'zzz.R'

**RoxygenNote** 5.0.1.9000

**NeedsCompilation** no

## R topics documented:

ImmuneSpaceR-package . . . . .	2
CreateConnection . . . . .	2
ImmuneSpaceConnection-class . . . . .	3
ISpalette . . . . .	5
loadConnection . . . . .	6
theme_IS . . . . .	6
write_netrc . . . . .	7
<b>Index</b>	<b>8</b>

---

ImmuneSpaceR-package    *A Thin Wrapper Around ImmuneSpace*

---

### Description

ImmuneSpaceR provides a convenient API for accessing data sets within the ImmuneSpace database.

### Details

Uses the Rlabkey package to connect to ImmuneSpace. Implements caching, and convenient methods for accessing data sets.

### Author(s)

Greg Finak

---

CreateConnection    *CreateConnection*

---

### Description

Constructor for ImmuneSpaceConnection class

### Usage

```
CreateConnection(study = NULL, login = NULL, password = NULL,
  verbose = FALSE)
```

### Arguments

study	A "character" vector naming the study.
login	A "character". Optional argument. If there is no netrc file a temporary one can be written by passing login and password of an active ImmuneSpace account.
password	A "character". Optional. The password for the selected login.
verbose	A "logical" whether to print the extra details for troubleshooting.

### Details

Instantiates an ImmuneSpaceConnection for study The constructor will try to take the values of the various 'labkey.\*' parameters from the global environment. If they don't exist, it will use default values. These are assigned to 'options', which are then used by the ImmuneSpaceConnection class.

### Value

an instance of an ImmuneSpaceConnection

### See Also

ImmuneSpaceConnection

**Examples**

```
## Not run:
# Single study
con <- CreateConnection("SDY269")
# Cross study
con <- CreateConnection("")

## End(Not run)

sdy <- try(CreateConnection("SDY269"))
if(inherits(sdy, "try-error")){
  print("Read the Introduction vignette for more information on how to set up
  a .netrc file.")
}
```

---

 ImmuneSpaceConnection-class

*The ImmuneSpaceConnection class*


---

**Description**

A connection represents a study or a set of studies available on ImmuneSpace. It provides function to download and display the data within these studies.

**Details**

Uses global variables `labkey.url.base`, and `labkey.url.path`, to access a study. `labkey.url.base` should be `https://www.immunespace.org/`. `labkey.url.path` should be `/Studies/studyname`, where 'studyname' is the accession number of the study. The `ImmuneSpaceConnection` will initialize itself, and look for a `.netrc` file in `"~/` the user's home directory. The `.netrc` file should contain a `machine`, `login`, and `password` entry to allow access to ImmuneSpace, where `machine` is the host name like `"www.immunespace.org"`.

**Value**

An instance of an `ImmuneSpaceConnection` for a study in `'labkey.url.path'`

**Fields**

`study` A character. The study accession number. Use an empty string (`""`) to create a connection at the project level.

`config` A list. Stores configuration of the connection object such as URL, path and username.

`available_datasets` A data.table. The table of datasets available in the connection object.

`data_cache` A list. Stores the data to avoid downloading the same tables multiple times.

`constants` A list. Used to store information regarding gene-expression data.

**Methods**

- `addTrt(x = NULL)` Add treatment information to the `phenoData` of an expression matrix available in the connection object.  
`x`: A character. The name of a expression matrix that has been downloaded from the connection.
- `clear_cache()` Clear the `data_cache`. Remove downloaded datasets and expression matrices.
- `EMNames(EM = NULL, colType = "participant_id")` Change the `sampleNames` of an `ExpressionSet` fetched by `getGEMatrix` using the information in the `phenoData` slot.  
`x`: An `ExpressionSet`, as returned by `getGEMatrix`.  
`colType`: A character. The type of column names. Valid options are `'expsample_accession'` and `'participant_id'`.
- `getDataset(x, original_view = FALSE, reload = FALSE, colFilter = NULL, ...)` Get a dataset from the connection  
`original_view`: A logical. If set to `TRUE`, download the `ImmPort` view. Else, download the default grid view.  
`reload`: A logical. Clear the cache. If set to `TRUE`, download the dataset, whether a cached version exist or not.  
`colFilter`: A character. A filter as returned by `Rlabkey`'s `makeFilter` function.  
`'...'`: Extra arguments to be passed to `labkey.selectRows`.
- `getGEAnalysis(...)` Downloads data from the gene expression analysis results table.  
`'...'`: A list of arguments to be passed to `labkey.selectRows`.
- `getGEFiles(files, destdir = ".")` Download gene expression raw data files.  
`files`: A character. Filenames as shown on the `gene_expression_files` dataset.  
`destdir`: A character. The local path to store the downloaded files.
- `getGEMatrix(x = NULL, cohort = NULL, summary = FALSE, reload = FALSE)` Downloads a normalized gene expression matrix from `ImmuneSpace`.  
`'x'`: A 'character'. The name of the gene expression matrix to download.  
`'cohort'`: A 'character'. The name of a cohort that has an associated gene expression matrix. Note that if `'cohort'` isn't `NULL`, then `'x'` is ignored. `'summary'`: A 'logical'. If set to `TRUE`, Downloads a matrix with expression averaged by gene symbol. `'reload'`: A 'logical'. If set to `TRUE`, the matrix will be downloaded again, even if a cached copy exist in the `ImmuneSpaceConnection` object.
- `listDatasets(which = c("datasets", "expression"))` List the datasets available in the study or studies of the connection.
- `listGEAnalysis()` List available gene expression analysis for the connection.
- `quick_plot(...)` Plots a selected dataset. This is the function used by the `DataExplorer` module on `ImmuneSpace`.  
`dataset`: A character. The name of the dataset to plot, as displayed by the `listDataset` method.  
`normalize_to_baseline`: A logical. If set to `TRUE`, the values are plotted as `log2` fold-change from baseline.  
`type`: A character. The type of plot. Valid choices are `'auto'`, `'heatmap'`, `'boxplot'`, `'lineplot'`, `'violinplot'`. If set to `'auto'`, the function will select an appropriate plot type for the selected data.  
`filter`: A filter as created by the `makeFilter` function from `Rlabkey`.  
`facet`: The faceting for `ggplot2` based plots. Valid choices are `'grid'` and `'wrap'`.  
`text_size`: The size of all text elements in the plot.

legend: A character. Columns of the dataset or demographics to be added as legend on the heatmap. This argument is ignored if the plot type isn't heatmap.

show\_virus\_strain: A logical. Should all the virus strains be shown or should the values be averaged. Only used when dataset = 'hai'.

'...': Extra argument to be passed to ggplot. e.g: shape = 'Age', color = 'Race'.

## See Also

[CreateConnection ImmuneSpaceR-package](#)

## Examples

```
## Not run:
sdy269 <- CreateConnection("SDY269")
sdy269

## End(Not run)
```

---

ISpalette

*ImmuneSpace palette*

---

## Description

Create a color gradient of the selected length that matches the ImmuneSpace theme.

## Usage

```
ISpalette(n)
```

## Arguments

n                    A numeric. The length of the desired palette.

## Value

A character vector colors in hexadecimal code of length n.

## Examples

```
plot(1:10, col = ISpalette(10), cex = 10, pch = 16)
```

---

loadConnection	<i>Save/Load an ImmuneSpaceConnection object from disk</i>
----------------	--

---

### Description

Connection can hold a lot of data in cache. If a lot of work has been done (e.g: lots of downloaded datasets and gene-expression matrices), it can be useful to save the connection for later work or even offline use.

### Usage

```
loadConnection(file)

saveConnection(con, file)
```

### Arguments

file	The file name to be saved to or loaded from
con	An ImmuneSpaceConnection. The connection to save to file. To be loaded later using loadConnection.

### Value

An ImmuneSpaceConnection object

### Examples

```
#Sample saved connection with pre-downloaded expression matrices and datasets
saved <- system.file("extdata/saved_con.rds", package = "ImmuneSpaceR")
new_con <- loadConnection(saved)
new_con
names(new_con$data_cache)
## Not run:
  saveConnection(new_con, tempfile())

## End(Not run)
```

---

theme_IS	<i>theme_IS</i>
----------	-----------------

---

### Description

Theme that matches ImmuneSpace's graphic style. The theme modifies the background, the grid lines, the axis, and the colors used by continuous and gradient scales.

### Usage

```
theme_IS(base_size = 12)
```

**Arguments**

`base_size`      A numeric. Base font size.

**Details**

List of modified ggplot2 elements: `panel.background`, `panel.grid.major`, `panel.grid.minor`, `axis.ticks`, `axis.line.x`, `axis.line.y`, `plot.title`, and `strip.background`.

The default `scale_fill_gradient`, `scale_fill_continuous`, `scale_colour_gradient` and `scale_colour_continuous` are also replaced by a custom scale.

**Value**

A theme object

**Examples**

```
library(ggplot2)
p <- ggplot(data = mtcars) + geom_point(aes(x = mpg, y = cyl, color = hp)) + facet_grid(vs ~ am)
p + theme_IS()
```

---

write\_netrc

*Write a netrc file*

---

**Description**

Write a netrc file that is valid for accessing ImmuneSpace

**Usage**

```
write_netrc(login, password, file = NULL)
```

**Arguments**

`login`            A character. The email address used for logging in on ImmuneSpace.

`password`        A character. The password associated with the login.

`file`            A character. The credentials will be written into that file. If left NULL, the netrc will be written into a temporary file.

**Examples**

```
write_netrc("immunespaceuser@gmail.com", "mypassword")
```

# Index

.ISCon (ImmuneSpaceConnection-class), 3  
addTrt (ImmuneSpaceConnection-class), 3  
CreateConnection, 2, 5  
EMNames (ImmuneSpaceConnection-class), 3  
getDataset  
    (ImmuneSpaceConnection-class),  
    3  
getGEAnalysis  
    (ImmuneSpaceConnection-class),  
    3  
getGEMatrix  
    (ImmuneSpaceConnection-class),  
    3  
ImmuneSpace  
    (ImmuneSpaceConnection-class),  
    3  
ImmuneSpaceConnection  
    (ImmuneSpaceConnection-class),  
    3  
ImmuneSpaceConnection-class, 3  
ImmuneSpaceR (ImmuneSpaceR-package), 2  
ImmuneSpaceR-package, 2  
ISpalette, 5  
listDatasets  
    (ImmuneSpaceConnection-class),  
    3  
listGEAnalysis  
    (ImmuneSpaceConnection-class),  
    3  
loadConnection, 6  
quick\_plot  
    (ImmuneSpaceConnection-class),  
    3  
saveConnection (loadConnection), 6  
theme\_IS, 6  
write\_netrc, 7