

BSgenome.Drerio.UCSC.danRer6

February 28, 2017

BSgenome.Drerio.UCSC.danRer6

Full genome sequences for Danio rerio (UCSC version danRer6)

Description

Full genome sequences for Danio rerio (Zebrafish) as provided by UCSC (danRer6, Dec. 2008) and stored in Biostrings objects.

Note

This BSgenome data package was made from the following source data files:

danRer6.fa.gz from <http://hgdownload.cse.ucsc.edu/goldenPath/danRer6/bigZips/>

See [?BSgenomeForge](#) and the BSgenomeForge vignette (`vignette("BSgenomeForge")`) in the **BSgenome** software package for how to make a BSgenome data package.

Author(s)

The Bioconductor Dev Team

See Also

- [BSgenome](#) objects and the [available.genomes](#) function in the **BSgenome** software package.
- [DNAString](#) objects in the **Biostrings** package.
- The BSgenomeForge vignette (`vignette("BSgenomeForge")`) in the **BSgenome** software package for how to make a BSgenome data package.

Examples

```
BSgenome.Drerio.UCSC.danRer6
genome <- BSgenome.Drerio.UCSC.danRer6
seqlengths(genome)
genome$chr1 # same as genome[["chr1"]]
```

```
## -----## Upstream sequences
## -----
```

```
## Starting with BioC 3.0, the upstream1000, upstream2000, and
## upstream5000 sequences for danRer6 are not included in the BSgenome
## data package anymore. However they can easily be extracted from the
## full genome sequences with something like:

library(GenomicFeatures)
txdb <- makeTranscriptDbFromUCSC("danRer6", "refGene")
gn <- sort(genes(txdb))
up1000 <- flank(gn, width=1000)
up1000seqs <- getSeq(genome, up1000)

## IMPORTANT: Make sure you use a TxDb package (or TranscriptDb object),
## that contains a gene model based on the exact same reference genome
## as the BSgenome object you pass to getSeq(). Note that you can make
## your own custom TranscriptDb object from various annotation resources.
## See the makeTranscriptDbFromUCSC(), makeTranscriptDbFromBiomart(),
## and makeTranscriptDbFromGFF() functions in the GenomicFeatures
## package.

## -----
## Genome-wide motif searching
## -----
## See the GenomeSearching vignette in the BSgenome software
## package for some examples of genome-wide motif searching using
## Biostrings and the BSgenome data packages:
if (interactive())
  vignette("GenomeSearching", package="BSgenome")
```

Index

*Topic **data**

BSgenome.Drerio.UCSC.danRer6, [1](#)

*Topic **package**

BSgenome.Drerio.UCSC.danRer6, [1](#)

available.genomes, [1](#)

BSgenome, [1](#)

BSgenome.Drerio.UCSC.danRer6, [1](#)

BSgenome.Drerio.UCSC.danRer6-package
(BSgenome.Drerio.UCSC.danRer6),
[1](#)

BSgenomeForge, [1](#)

DNAStrng, [1](#)

Drerio (BSgenome.Drerio.UCSC.danRer6), [1](#)