

Package ‘fgsea’

April 15, 2019

Title Fast Gene Set Enrichment Analysis

Version 1.8.0

Date 2018-02-21

Description The package implements an algorithm for fast gene set enrichment analysis. Using the fast algorithm allows to make more permutations and get more fine grained p-values, which allows to use accurate standard approaches to multiple hypothesis correction.

biocViews GeneExpression, DifferentialExpression, GeneSetEnrichment, Pathways

SystemRequirements C++11

Depends R (>= 3.3), Rcpp

Imports data.table, BiocParallel, stats, ggplot2 (>= 2.2.0), gridExtra, grid, fastmatch, Matrix, utils

Suggests testthat, knitr, rmarkdown, reactome.db, AnnotationDbi, parallel, org.Mm.eg.db, limma, GEOquery

License MIT + file LICENCE

LazyData true

LinkingTo Rcpp

RoxygenNote 6.0.1

VignetteBuilder knitr

URL <https://github.com/ctlab/fgsea/>

BugReports <https://github.com/ctlab/fgsea/issues>

git_url <https://git.bioconductor.org/packages/fgsea>

git_branch RELEASE_3_8

git_last_commit bb2898a

git_last_commit_date 2018-10-30

Date/Publication 2019-04-15

Author Gennady Korotkevich [ctb],
Alexey Sergushichev [aut, cre]

Maintainer Alexey Sergushichev <alsergbox@gmail.com>

R topics documented:

calcGseaStat	2
calcGseaStatBatchCpp	3
collapsePathways	3
examplePathways	4
exampleRanks	4
fgsea	4
fgseaLabel	6
gmtPathways	7
plotEnrichment	8
plotGseaTable	8
reactomePathways	9

Index	10
--------------	-----------

calcGseaStat	<i>Calculates GSEA statistics for a given query gene set</i>
--------------	--

Description

Takes $O(k \log k)$ time, where k is a size of ‘selectedSize’.

Usage

```
calcGseaStat(stats, selectedStats, gseaParam = 1, returnAllExtremes = FALSE,
  returnLeadingEdge = FALSE)
```

Arguments

stats	Named numeric vector with gene-level statistics sorted in decreasing order (order is not checked).
selectedStats	Indexes of selected genes in the ‘stats’ array.
gseaParam	GSEA weight parameter (0 is unweighted, suggested value is 1).
returnAllExtremes	If TRUE return not only the most extreme point, but all of them. Can be used for enrichment plot
returnLeadingEdge	If TRUE return also leading edge genes.

Value

Value of GSEA statistic if both returnAllExtremes and returnLeadingEdge are FALSE. Otherwise returns list with the following elements:

- res – value of GSEA statistic
- tops – vector of top peak values of cumulative enrichment statistic for each gene;
- bottoms – vector of bottom peak values of cumulative enrichment statistic for each gene;
- leadingGene – vector with indexes of leading edge genes that drive the enrichment, see http://software.broadinstitute.org/gsea/doc/GSEAUserGuideTEXT.htm#_Running_a_Leading.

Examples

```
data(exampleRanks)
data(examplePathways)
ranks <- sort(exampleRanks, decreasing=TRUE)
es <- calcGseaStat(ranks, na.omit(match(examplePathways[[1]], names(ranks))))
```

calcGseaStatBatchCpp *Calculates GSEA statistic value for all gene sets in 'selectedStats' list.*

Description

Takes $O(n + mK \log K)$ time, where n is the number of genes, m is the number of gene sets, and k is the mean gene set size.

Usage

```
calcGseaStatBatchCpp(stats, selectedGenes, geneRanks)
```

Arguments

stats	Numeric vector of gene-level statistics sorted in decreasing order
selectedGenes	List of integer vector with integer gene IDs (from 1 to n)
geneRanks	Integer vector of gene ranks

Value

Numeric vector of GSEA statistics of the same length as 'selectedGenes' list

collapsePathways *Collapse list of enriched pathways to independent ones.*

Description

Collapse list of enriched pathways to independent ones.

Usage

```
collapsePathways(fgseaRes, pathways, stats, pval.threshold = 0.05,
  nperm = 10/pval.threshold, gseaParam = 1)
```

Arguments

fgseaRes	Table with results of running fgsea(), should be filtered by p-value, for example by selecting ones with $\text{padj} < 0.01$.
pathways	List of pathways, should contain all the pathways present in 'fgseaRes'.
stats	Gene-level statistic values used for ranking, the same as in 'fgsea()'.
pval.threshold	Two pathways are considered dependent when p-value of enrichment of one pathways on background of another is greater than 'pval.threshold'.
nperm	Number of permutations to test for independence, should be several times greater than '1/pval.threshold'. Default value: '10/pval.threshold'.
gseaParam	GSEA parameter, same as for 'fgsea()'

Value

Named list with two elements: 'mainPathways' containing IDs of pathways not reducible to each other, and 'parentPathways' with vector describing for all the pathways to which ones they can be reduced. For pathways from 'mainPathways' vector 'parentPathways' contains 'NA' values.

Examples

```
data(examplePathways)
data(exampleRanks)
fgseaRes <- fgsea(examplePathways, exampleRanks, nperm=10000, maxSize=500)
collapsedPathways <- collapsePathways(fgseaRes[order(pval)][padj < 0.01],
                                     examplePathways, exampleRanks)
mainPathways <- fgseaRes[pathway %in% collapsedPathways$mainPathways][
  order(-NES), pathway]
```

examplePathways	<i>Example list of mouse Reactome pathways.</i>
-----------------	---

Description

The list was obtained by selecting all the pathways from 'reactome.db' package that contain mouse genes. The exact script is available as `system.file("gen_reactome_pathways.R", package="fgsea")`

exampleRanks	<i>Example vector of gene-level statistics obtained for Th1 polarization.</i>
--------------	---

Description

The data were obtained by doing differential expression between Naive and Th1-activated states for GEO dataset GSE14308. The exact script is available as `system.file("gen_gene_ranks.R", package="fgsea")`

fgsea	<i>Runs preranked gene set enrichment analysis.</i>
-------	---

Description

The function takes about $O(nk^{3/2})$ time, where n is number of permutations and k is a maximal size of the pathways. That means that setting 'maxSize' parameter with a value of ~500 is strongly recommended.

Usage

```
fgsea(pathways, stats, nperm, minSize = 1, maxSize = Inf, nproc = 0,
      gseaParam = 1, BPPARAM = NULL)
```

Arguments

pathways	List of gene sets to check.
stats	Named vector of gene-level stats. Names should be the same as in 'pathways'
nperm	Number of permutations to do. Minimal possible nominal p-value is about 1/nperm
minSize	Minimal size of a gene set to test. All pathways below the threshold are excluded.
maxSize	Maximal size of a gene set to test. All pathways above the threshold are excluded.
nproc	If not equal to zero sets BPPARAM to use nproc workers (default = 0).
gseaParam	GSEA parameter value, all gene-level statis are raised to the power of 'gsea-Param' before calculation of GSEA enrichment scores.
BPPARAM	Parallelization parameter used in bplapply. Can be used to specify cluster to run. If not initialized explicitly or by setting 'nproc' default value 'bpparam()' is used.

Value

A table with GSEA results. Each row corresponds to a tested pathway. The columns are the following:

- pathway – name of the pathway as in 'names(pathway)';
- pval – an enrichment p-value;
- padj – a BH-adjusted p-value;
- ES – enrichment score, same as in Broad GSEA implementation;
- NES – enrichment score normalized to mean enrichment of random samples of the same size;
- nMoreExtreme – a number of times a random gene set had a more extreme enrichment score value;
- size – size of the pathway after removing genes not present in 'names(stats)';
- leadingEdge – vector with indexes of leading edge genes that drive the enrichment, see http://software.broadinstitute.org/gsea/doc/GSEAUserGuideTEXT.htm#_Running_a_Leading.

Examples

```
data(examplePathways)
data(exampleRanks)
fgseaRes <- fgsea(examplePathways, exampleRanks, nperm=10000, maxSize=500)
# Testing only one pathway is implemented in a more efficient manner
fgseaRes1 <- fgsea(examplePathways[1], exampleRanks, nperm=10000)
```

fgseaLabel	<i>Runs label-permuring gene set enrichment analysis.</i>
------------	---

Description

Runs label-permuring gene set enrichment analysis.

Usage

```
fgseaLabel(pathways, mat, labels, nperm, minSize = 1, maxSize = Inf,
           nproc = 0, gseaParam = 1, BPPARAM = NULL)
```

Arguments

pathways	List of gene sets to check.
mat	Gene expression matrix. Row name should be the same as in 'pathways'
labels	Numeric vector of labels for the correlation score of the same length as the number of columns in 'mat'
nperm	Number of permutations to do. Minimal possible nominal p-value is about 1/nperm
minSize	Minimal size of a gene set to test. All pathways below the threshold are excluded.
maxSize	Maximal size of a gene set to test. All pathways above the threshold are excluded.
nproc	If not equal to zero sets BPPARAM to use nproc workers (default = 0).
gseaParam	GSEA parameter value, all gene-level statis are raised to the power of 'gseaParam' before calculation of GSEA enrichment scores.
BPPARAM	Parallelization parameter used in bplapply. Can be used to specify cluster to run. If not initialized explicitly or by setting 'nproc' default value 'bpparam()' is used.

Value

A table with GSEA results. Each row corresponds to a tested pathway. The columns are the following:

- pathway – name of the pathway as in 'names(pathway)';
- pval – an enrichment p-value;
- padj – a BH-adjusted p-value;
- ES – enrichment score, same as in Broad GSEA implementation;
- NES – enrichment score normalized to mean enrichment of random samples of the same size;
- nMoreExtreme – a number of times a random gene set had a more extreme enrichment score value;
- size – size of the pathway after removing genes not present in 'names(stats)';
- leadingEdge – vector with indexes of leading edge genes that drive the enrichment, see http://software.broadinstitute.org/gsea/doc/GSEAUUserGuideTEXT.htm#_Running_a_Leading.

Examples

```
library(limma)
library(GEOquery)
es <- getGEO("GSE19429", AnnotGPL = TRUE)[[1]]
exprs(es) <- normalizeBetweenArrays(log2(exprs(es)+1), method="quantile")
es <- es[!grepl("///", fData(es)$`Gene ID`), ]
es <- es[fData(es)$`Gene ID` != "", ]
es <- es[order(apply(exprs(es), 1, mean), decreasing=TRUE), ]
es <- es[!duplicated(fData(es)$`Gene ID`), ]
rownames(es) <- fData(es)$`Gene ID`

pathways <- reactomePathways(rownames(es))
mat <- exprs(es)
labels <- as.numeric(as.factor(gsub(".*", "", es$title)))
fgseaRes <- fgseaLabel(pathways, mat, labels, nperm = 1000, minSize = 15, maxSize = 500)
```

gmtPathways

Returns a list of pathways from a GMT file.

Description

Returns a list of pathways from a GMT file.

Usage

```
gmtPathways(gmt.file)
```

Arguments

gmt.file Path to a GMT file.

Value

A list of vectors with gene sets.

Examples

```
pathways <- gmtPathways(system.file(
  "extdata", "mouse.reactome.gmt", package="fgsea"))
```

plotEnrichment *Plots GSEA enrichment plot.*

Description

Plots GSEA enrichment plot.

Usage

```
plotEnrichment(pathway, stats, gseaParam = 1, ticksSize = 0.2)
```

Arguments

pathway	Gene set to plot.
stats	Gene-level statistics.
gseaParam	GSEA parameter.
ticksSize	width of vertical line corresponding to a gene (default: 0.2)

Value

ggplot object with the enrichment plot.

Examples

```
data(examplePathways)
data(exampleRanks)
## Not run:
plotEnrichment(examplePathways[["5991130_Programmed_Cell_Death"]],
                exampleRanks)

## End(Not run)
```

plotGseaTable *Plots table of enrichment graphs using ggplot and gridExtra.*

Description

Plots table of enrichment graphs using ggplot and gridExtra.

Usage

```
plotGseaTable(pathways, stats, fgseaRes, gseaParam = 1, colwidths = c(5, 3,
0.8, 1.2, 1.2))
```


Arguments

pathways	Pathways to plot table, as in 'fgsea' function.
stats	Gene-level stats, as in 'fgsea' function.
fgseaRes	Table with fgsea results.
gseaParam	GSEA-like parameter. Adjusts displayed statistic values, values closer to 0 flatten plots. Default = 1, value of 0.5 is a good choice too.
colwidths	Vector of five elements corresponding to column width for grid.arrange. If column width is set to zero, the column is not drawn.

Value

TableGrob object returned by grid.arrange.

Examples

```
data(examplePathways)
data(exampleRanks)
fgseaRes <- fgsea(examplePathways, exampleRanks, nperm=1000,
                 minSize=15, maxSize=100)
topPathways <- fgseaRes[head(order(pval), n=15)][order(NES), pathway]
## Not run:
plotGseaTable(examplePathways[topPathways], exampleRanks,
              fgseaRes, gseaParam=0.5)

## End(Not run)
```

reactomePathways	<i>Returns a list of Reactome pathways for given Entrez gene IDs</i>
------------------	--

Description

Returns a list of Reactome pathways for given Entrez gene IDs

Usage

```
reactomePathways(genes)
```

Arguments

genes	Entrez IDs of query genes.
-------	----------------------------

Value

A list of vectors with gene sets.

Examples

```
data(exampleRanks)
pathways <- reactomePathways(names(exampleRanks))
```

Index

[calcGseaStat](#), [2](#)
[calcGseaStatBatchCpp](#), [3](#)
[collapsePathways](#), [3](#)

[examplePathways](#), [4](#)
[exampleRanks](#), [4](#)

[fgsea](#), [4](#)
[fgseaLabel](#), [6](#)

[gmtPathways](#), [7](#)

[plotEnrichment](#), [8](#)
[plotGseaTable](#), [8](#)

[reactomePathways](#), [9](#)