

# Package ‘levi’

April 16, 2019

**Type** Package

**Title** Landscape Expression Visualization Interface

**Version** 1.0.0

**Author** Jose Rafael Pilan <rafael.pilan@unesp.br>, Agnes Alessandra Sekijima Takeda <agnes.takeda@unesp.br>, Jose Luiz Rybarczyk Filho <jose.lui@unesp.br>

**Maintainer** Jose Luiz Rybarczyk Filho <jose.lui@unesp.br>

**Description** The tool integrates data from biological networks with transcriptomes, displaying a heatmap with surface curves to evidence the altered regions.

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 6.1.0

**Depends** R(>= 3.5.0)

**Imports** DT(>= 0.4), RColorBrewer(>= 1.1-2), colorspace(>= 1.3-2), dplyr(>= 0.7.4), ggplot2(>= 2.2.1), httr(>= 1.3.1), igraph(>= 1.2.1), reshape2(>= 1.4.3), shiny(>= 1.0.5), shinydashboard(>= 0.7.0), shinyjs(>= 1.0), xml2(>= 1.2.0), knitr, Rcpp (>= 0.12.18), grid, grDevices, stats, utils, testthat

**LinkingTo** Rcpp

**License** GPL (>= 2)

**biocViews** GeneExpression, Sequencing, Network

**VignetteBuilder** knitr

**LazyLoad** yes

**NeedsCompilation** no

**git\_url** <https://git.bioconductor.org/packages/levi>

**git\_branch** RELEASE\_3\_8

**git\_last\_commit** 0a68eb6

**git\_last\_commit\_date** 2018-10-30

**Date/Publication** 2019-04-15

## R topics documented:

levi . . . . .	2
LEVIui . . . . .	3
readExpColumn . . . . .	4

**Index****5**


---

levi	<i>levi</i>
------	-------------

---

**Description**

This is the Levi script mode. It allows you to create the integration of networks and gene expression levels as batch processing

**Usage**

```
levi(expressionInput, fileTypeInput, networkCoordinatesInput,
networkInteractionsInput, geneSymbolInput, readExpColumn,
contrastValueInput, zoomValueInput, resolutionValueInput,
smoothValueInput, expressionLog, contourLevi, setcolor)
```

**Arguments**

expressionInput	Filename of gene expression data, which is a numeric data.frame or matrix. The rows represent genes/proteins and the columns represent the experiment (RNA-seq, microarray, etc).
fileTypeInput	Filename of biological network. Levi can read files written in the following formats: Medusa (DAT), RedeR (DYN), Pajek (NET) and STRING/STITCH
networkCoordinatesInput	It allows the user to load the coordinate of the nodes the network.
networkInteractionsInput	Parameter available only to STRING/STITCH data format. It allows the user to load the interaction data file of the network.
geneSymbolInput	Column name from gene expression data containing the identifier (gene Symbol, Entrez ID, EMSEMBL, etc).
readExpColumn	Variable from readExpColumn function containing the comparisons of the experiments
contrastValueInput	Numeric value for image contrast. The variable range is 0 to 100. The default value is 50
zoomValueInput	Numeric value for image zoom. The variable range is 0 to 100. The default value is 50.
resolutionValueInput	Numeric value for image resolution. The variable range is 0 to 100. The default value is 50.
smoothValueInput	Numeric value for image smoothness. The variable range is 0 to 100. The default is 50.
expressionLog	Logical variable to indicate Log2 normalization in the expression levels. The default is FALSE
contourLevi	Logical variable to allow contour lines. The default is TRUE.
setcolor	Select the color palette to build the heatmat. The options available are: default, terrain, rainbow, heat, topo and cm.

**Details**

Integrates the biological network and gene expression levels (or other type of data)

**Value**

Return a image (heatmap).

**Author(s)**

José Rafael Pilan (rafael.pilan@unesp.br)

**Examples**

```
template_network <- file.path(system.file(package="levi"), "extdata",
  "medusa.dat", fsep = .Platform$file.sep)
template_expression <- file.path(system.file(package="levi"),
  "extdata", "expression.dat", fsep = .Platform$file.sep)
landscape <- levi(networkCoordinatesInput = template_network,
  expressionInput = template_expression, fileTypeInput = "dat",
  geneSymbolInput = "ID",
  readExpColumn=readExpColumn("TumorCurrentSmoker-NormalNeverSmoker"),
  contrastValueInput = 50, resolutionValueInput = 50, zoomValueInput = 50,
  smoothValueInput = 50, expressionLog = FALSE, contourLevi = TRUE,
  setcolor = "default")
```

---

 LEVIui

*LEVIui*


---

**Description**

Launch the Levi Graphical User Interface (GUI) in local machine.

**Usage**

```
LEVIui(browser)
```

**Arguments**

browser	This argument is necessary to launch Levi GUI. To launch Levi in the web browser the argument required "TRUE". To launch Levi in the R environment the argument required "FALSE". The default is "FALSE"
---------	--

**Details**

This function launch the LEVI Graphical User Interface. The interface provides the same tools available in the script mode. There are two tools only available in the user interface: 1) Selection of area from heatmap to calculate the gene expression levels in the area selected; 2) Selection of the genes in some specific area from the image.

**Value**

return a GUI

**Author(s)**

José Rafael Pilan <rafael.pilan@unesp.br>

**Examples**

```
LEVIui(browser)
#LEVIui(browser=TRUE) #Launch Levi to Browser.
#LEVIui(browser=FALSE) #Launch Levi to R environment.
```

---

readExpColumn	<i>readExpColumn</i>
---------------	----------------------

---

**Description**

This function helps to prepare the data in the script mode. It also allows the obtention of dataset plot as a batch processing.

**Usage**

```
readExpColumn(x, ...)
```

**Arguments**

x	Names of two expression datasets to be compared. They should be separated by hyphen (-)
...	To add more comparisons, each combination must be separated by comma (,).

**Details**

List the names of the expression datasets that will be used for comparison

**Value**

Returns the names of comparisons to be used by Levi

**Note**

To generate a plot from a single dataset, the name of the sample must be informed twice (Ex. "CaseA-CaseA")

**Author(s)**

José Rafael Pilan (rafael.pilan@unesp.br)

**Examples**

```
base <- readExpColumn(a="NormalNeverSmoker-NormalNeverSmoker")
```

# Index

levi, [2](#)

LEVIui, [3](#)

readExpColumn, [4](#)